

Plasma Panel Display Modules

16 Character Display with Drive Electronics and Controller



The APD-016M040 has two modes of operation, parallel or serial input. The parallel interface consists of a 6 bit data bus plus 3 hand-shaking and 3 control lines. New characters are entered from right to left by presenting the appropriate 6 bit code to the data bus and latching it into memory with a DATA PRESENT pulse. A WRITE CYCLE output signal is provided during the time in which data can be written to the display, and a DATA TAKEN pulse occurs after data has been accepted, or when BACK SPACE occurs. BACK SPACE allows the displayed message to be shifted to the right, recalling the last character shifted off the left end of the display. Up to 16 characters may be recalled, after which blanks are entered in the left position of the display. The display may be cleared at any time by bringing the CLEAR line low. A BLANK DISABLE line is provided to blank the display without altering the refresh memory contents.

The serial interface is RS-232-C compatible and has 3 selectable baud rates (300, 1200, 9600). This mode assumes 1 start bit, 8 data bits, 1 stop bit, no parity and half duplex. No handshaking is provided. Mode settings and baud rates are selected as follows. (Both lines are internally pulled to Vcc with 6.8 kilohm pull-up resistors.)

SS0	SS1	BAUD RATE
0	0	300
0	1	1200
1	0	9600
1	1	Parallel

FEATURES

- 16 (1 x 16) alphanumeric characters (5 x 7 dot matrix).
- Bezel and filter included.
- Parallel and serial interfaces.
- High brightness.
- Wide viewing angle (150°).
- Low input voltage.
- Compact size.
- Enhanced replacement for Burroughs SSD1000-0061 (optionally-0041).

PIN DESCRIPTION

PIN	DESCRIPTION	PIN	DESCRIPTION
1	DATA BIT 5	A	DATA BIT 4
2	DATA BIT 3	B	DATA BIT 2
3	DATA BIT 1	C	DATA BIT 0
4	N/C	D	DATA PRESENT
5	CLEAR	E	BACK SPACE
6	SPEED SELECT 1	F	DATA TAKEN
7	WRITE CYCLE	H	RECEIVED DATA
8	BLANK DISABLE	J	+ 5 V
9	SPEED SELECT 0	K	N/C
10	N/C	L	GND

Keyway between pins 4 (D) and 5 (E).

OPTICAL SPECIFICATIONS

Viewing Area: 0.40" [10.2mm] W x 6.69" [169.9mm] L.

Number of Characters: 16.

Character Size: 0.28" [7.1mm] W x 0.40" [10.2mm] H.

Pixel Size: 0.036" [0.914mm] diameter.

Pixel Pitch: 0.061" [1.55mm].

Character Spacing: 2 blank columns between successive characters - 0.147" [3.73mm].

Luminance: 80 foot lamberts.


STANDARD ELECTRICAL SPECIFICATIONS

	SYMBOL	MIN.	TYP.	MAX.	UNITS
Supply Voltage	VCC	4.75	5	5.25	V
Supply Current (1)	ICC	—	1.25	1.75	A
Logic One Voltage	VIH	2	—	—	V
Logic 0 Voltage	VIL	—	—	0.8	V

*Vcc is the input to a DC-DC converter.

There may be peak in rush currents higher than shown.

DIMENSIONS in inches [millimeters]



ORDERING INFORMATION

DESCRIPTION

PART NO.

Display and Electronics (includes Bezel) (Equivalent to Burroughs SSD1000-0061)	APD-016M040
Display and Electronics (includes Bezel) Data Entry is Left to Right (Equivalent to Burroughs SSD1000-0041)	APD-016M040-1
Mating Connector	280498-01



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.