


SD



NOTES:

1. FOR USE WITH RG-55B, 142B, & 223/U CABLE.
2. FOR CRIMPING USE DIE KTH-2001.
3. FOR CABLING INSTRUCTIONS SEE CP-403.
4. MARK PACKAGE: KINGS KD-59-64
YRWK (DATE CODE)
5. MATERIALS:
INSULATOR: TEFLON, ASTM-D-1457
GASKET: SIL. RUB., ZZ-R-765
K-GRIP SLEEVE: COM. BRONZE TUBE, ALLOY 220
OUTER CONTACT BER. COP., QQ-C-530
SPRING WASHER BER. COP., QQ-C-533
ALL OTHER METAL PARTS: BRASS, QQ-B-626
6. FINISHES:
CENTER CONTACT: HARD GOLD PLT. PER MIL-G-45204
ALL OTHER METAL PARTS: SILVER PLATE, QQ-S-365
7. ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
VOLTAGE RATING: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHz

KD-59-64

REVISIONS

ISSUE	CHANGES
0	ER 9550 WLA 04/05/71
1	CN 15144 A JL 02/06/76
2	CN 37575 C REDRAWN MK 02/11/99
3	CN 40053 C PMC 08/28/07

SCALE 4:1

APPROX SURFACE AREA

USED ON

REF:

C-PLUG

DRAWN WLA DATE 04/02/71

DESIGN LJ DATE 04/05/71

APPR. DATE

KD-59-64

SD