


- Series 142 Pin Headers have double ended .018" diameter pluggable solder tails.
- Used to interconnect PC Boards with spacings of .210", .335", .585" or .835". (MM# 4259-1, -2, -3 or -4 pin). See page 170 for details.



Total number of pins				Quantity per tube	Ordering Information			
	A	B	C		L=.210	L=.335	L=.585	L=.835
6	0.3	0.3	0.4	67	142-XX-306-00-591	142-XX-306-00-592	142-XX-306-00-593	142-XX-306-00-594
8	0.4	0.3	0.4	50	142-XX-308-00-591	142-XX-308-00-592	142-XX-308-00-593	142-XX-308-00-594
14	0.7	0.3	0.4	29	142-XX-314-00-591	142-XX-314-00-592	142-XX-314-00-593	142-XX-314-00-594
16	0.8	0.3	0.4	25	142-XX-316-00-591	142-XX-316-00-592	142-XX-316-00-593	142-XX-316-00-594
18	0.9	0.3	0.4	22	142-XX-318-00-591	142-XX-318-00-592	142-XX-318-00-593	142-XX-318-00-594
20	1.0	0.3	0.4	40	142-XX-320-00-591	142-XX-320-00-592	142-XX-320-00-593	142-XX-320-00-594
24	1.2	0.3	0.4	17	142-XX-324-00-591	142-XX-324-00-592	142-XX-324-00-593	142-XX-324-00-594
22	1.1	0.4	0.5	14	142-XX-422-00-591	142-XX-422-00-592	142-XX-422-00-593	142-XX-422-00-594
24	1.2	0.6	0.7	16	142-XX-624-00-591	142-XX-624-00-592	142-XX-624-00-593	142-XX-624-00-594
28	1.4	0.6	0.7	14	142-XX-628-00-591	142-XX-628-00-592	142-XX-628-00-593	142-XX-628-00-594
32	1.6	0.6	0.7	12	142-XX-632-00-591	142-XX-632-00-592	142-XX-632-00-593	142-XX-632-00-594
40	2.0	0.6	0.7	10	142-XX-640-00-591	142-XX-640-00-592	142-XX-640-00-593	142-XX-640-00-594

**XX= Plating Code  
See Below**

**For High  
Temperature  
Insulators  
Add '100'  
To End Of  
Part Numbers**

SPECIFY PLATING CODE XX=	<b>10</b>	<b>90</b>		
Pin Plating	10μ" Au	200μ" Sn/Pb		