

# FOHLLUCAK

---

LazrSPEED® 150 LC Uniboot to Unconnectorized, ReadyPATCH® Ruggedized Fanout, 72-Fiber, Plenum

## Product Classification

<b>Portfolio</b>	Uniprise®
<b>Brand</b>	LazrSPEED®   ReadyPATCH®
<b>Product Type</b>	Fiber fanout cable assembly
<b>Regional Availability</b>	North America

## Construction Materials

<b>Fiber Type</b>	OM2, bend insensitive
<b>Total Fibers, quantity</b>	72
<b>Fibers per Subunit, quantity</b>	12
<b>Furcation Color</b>	Aqua

## Dimensions

<b>Cord Length, maximum</b>	999 ft   999 m
<b>Cord Length, minimum</b>	3 m   8 ft
<b>Ordering Note</b>	For lengths greater than 999 ft (304 m), orders must be in meters   Minimum length may vary based on cable configuration

## Environmental Specifications

<b>Environmental Space</b>	Plenum
<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)

## General Specifications

<b>Interface, connector A</b>	LC/UPC
<b>Interface, connector B</b>	Unterminated
<b>Color, connector A</b>	Beige
<b>Construction Type</b>	ReadyPATCH® ruggedized fanout, indoor
<b>Cord Configurator</b>	Yes
<b>Interface Feature, connector A</b>	Uniboot

## Mechanical Specifications

<b>Cable Retention Strength, maximum</b>	4.40 lb @ 90 ° 11.24 lb @ 0 °
--	----------------------------------

## Regulatory Compliance/Certifications

# FOHUUUCAA

---

## Agency

RoHS 2011/65/EU  
ISO 9001:2015

## Classification

Compliant  
Designed, manufactured and/or distributed under this quality management system



## Included Products

P-072-MP-5M-F12 (Product Component—not orderable) — LazrSPEED® Plenum MPO Trunk Cable, 72 fiber multi-unit with 12 fiber subunits

- CS-5M-MP (Product Component—not orderable) — LazrSPEED® 150 OM2+ Bend-Insensitive Multimode Fiber

460125206 (Product Component—not orderable) — TeraSPEED® Pre-Radiused LC Connector duplex for 1.6 mm Fiber, single-mode