

Window-type current transformer, Class 1 300 A/1 A, 5 VA



Figure similar

Model	
Product brand name	SENTRON
Product designation	Window-type current transformers
Operating apparent output / rated value	5 V·A
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	T
Protection class	
Protection class IP	IP20
<ul style="list-style-type: none"> <li>• Ratio of input current/output current</li> <li>• Current / at output / rated value</li> <li>• Current / at input / rated value</li> </ul>	300/1 A 1 A 300 A
Accuracy class / of the current transformer	class 1
Product feature / Touch protection	Yes
Connections	
Type of electrical connection / at output	screw-type terminals
Mechanical Design	

Height	85.5 mm
Width	64 mm
Width	
<ul style="list-style-type: none"> <li>• of the push-through bus bar / at 1 bus bar / maximum</li> </ul>	30 mm
<ul style="list-style-type: none"> <li>• of the push-through bus bar / in case of 2 bus bars / maximum</li> </ul>	25 mm
Depth	80 mm
Mounting type	screw fixing
Outer diameter / of the push-through conductor / maximum	28 mm

## Certificates

Reference code

- acc. to DIN EN 61346-2

T

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4NC5224-0CE20>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/4NC5224-0CE20>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=4NC5224-0CE20](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4NC5224-0CE20)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>