

# FAMLCUC01

---

## OptiSPEED® LC to Unconnectorized, Fiber Pigtail, 0.9 mm Tight Buffer

### Product Classification

<b>Portfolio</b>	CommScope®
<b>Brand</b>	OptiSPEED®
<b>Product Type</b>	Fiber pigtail, simplex
<b>Regional Availability</b>	Asia   Australia/New Zealand   EMEA   Latin America   North America

### Construction Materials

<b>Fiber Type</b>	OM1
<b>Total Fibers, quantity</b>	1

### Dimensions

<b>Cord Length, maximum</b>	23 ft   7 m
<b>Cord Length, minimum</b>	2 ft   1 m
<b>Ordering Note</b>	For lengths greater than 999 ft (304 m), orders must be in meters   Minimum length may vary based on cable configuration

### Environmental Specifications

<b>Environmental Space</b>	Plenum
<b>Operating Temperature</b>	-10 °C to +60 °C (+14 °F to +140 °F)

### General Specifications

<b>Construction Type</b>	Pigtail, unjacketed
<b>Interface, connector A</b>	LC/UPC
<b>Interface, connector B</b>	Unterminated
<b>Color, connector A</b>	Beige

### Mechanical Specifications

<b>Cable Retention Strength, maximum</b>	1.00 lb @ 0 ° 1.00 lb @ 90 °
--	---------------------------------

### Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
RoHS 2011/65/EU	Compliant
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system



## Included Products

X-TB-6F (Product Component—not orderable) — OptiSPEED® 900µm Tight Buffered Fiber

- CS-6F-TB (Product Component—not orderable) — OptiSPEED® OM1 Multimode Fiber

460125271 (Product Component—not orderable) — Behind The Wall Pre-Radiused LC Connector for 0.9 mm Fiber, multimode