


MITSUBISHI Nch POWER MOSFET

FS50KMH-06

HIGH-SPEED SWITCHING USE


FS50KMH-06



- ∨ 2.5V DRIVE
- ∨ V_{DSS} 60V
- ∨ r_{DS (ON)} (MAX) 21mΩ
- ∨ I_D 50A
- ∨ Integrated Fast Recovery Diode (TYP.) 75ns
- ∨ V_{iso} 2000V

OUTLINE DRAWING

Dimensions in mm



TO-220FN

APPLICATION

Motor control, Lamp control, Solenoid control
DC-DC converter, etc.

MAXIMUM RATINGS (T_C = 25°C)

Symbol	Parameter	Conditions	Ratings	Unit
V _{DSS}	Drain-source voltage	V _{GS} = 0V	60	V
V _{GSS}	Gate-source voltage	V _{DS} = 0V	±10	V
I _D	Drain current		50	A
I _{DM}	Drain current (Pulsed)		200	A
I _{DA}	Avalanche drain current (Pulsed)	L = 100μH	50	A
I _S	Source current		50	A
I _{SM}	Source current (Pulsed)		200	A
P _D	Maximum power dissipation		30	W
T _{ch}	Channel temperature		-55 ~ +150	°C
T _{stg}	Storage temperature		-55 ~ +150	°C
V _{iso}	Isolation voltage	AC for 1minute, Terminal to case	2000	V
—	Weight	Typical value	2.0	g

Feb.1999





FS50KMH-06

HIGH-SPEED SWITCHING USE

ELECTRICAL CHARACTERISTICS (T_{ch} = 25°C)







Symbol	Parameter	Test conditions	Limits			Unit
			Min.	Typ.	Max.	
V _{(BR)DSS}	Drain-source breakdown voltage	I _D = 1mA, V _{GS} = 0V	60	—	—	V
I _{GSS}	Gate-source leakage current	V _{GS} = ±20V, V _{DS} = 0V	—	—	±0.1	μA
I _{DSS}	Drain-source leakage current	V _{DS} = 60V, V _{GS} = 0V	—	—	0.1	mA
V _{GS(th)}	Gate-source threshold voltage	I _D = 1mA, V _{DS} = 10V	0.6	0.9	1.2	V
r _{DS(on)}	Drain-source on-state resistance	I _D = 25A, V _{GS} = 4V	—	15	21	mΩ
r _{DS(on)}	Drain-source on-state resistance	I _D = 25A, V _{GS} = 2.5V	—	18	25	mΩ
V _{DS(on)}	Drain-source on-state voltage	I _D = 25A, V _{GS} = 4V	—	0.375	0.525	V
y _{fs}	Forward transfer admittance	I _D = 25A, V _{DS} = 10V	—	53	—	S
C _{iss}	Input capacitance	V _{DS} = 10V, V _{GS} = 0V, f = 1MHz	—	4000	—	pF
C _{oss}	Output capacitance		—	590	—	pF
C _{rss}	Reverse transfer capacitance		—	320	—	pF
t _{d(on)}	Turn-on delay time	V _{DD} = 30V, I _D = 25A, V _{GS} = 4V, R _{GEN} = R _{GS} = 50Ω	—	55	—	ns
t _r	Rise time		—	190	—	ns
t _{d(off)}	Turn-off delay time		—	340	—	ns
t _f	Fall time		—	260	—	ns
V _{SD}	Source-drain voltage	I _S = 25A, V _{GS} = 0V	—	1.0	1.5	V
R _{th(ch-c)}	Thermal resistance	Channel to case	—	—	4.17	°C/W
t _{rr}	Reverse recovery time	I _S = 50A, dis/dt = -100A/μs	—	75	—	ns

PERFORMANCE CURVES



FS50KMH-06


HIGH-SPEED SWITCHING USE




FS50KMH-06

HIGH-SPEED SWITCHING USE


GATE-SOURCE VOLTAGE VS. GATE CHARGE (TYPICAL)




SOURCE-DRAIN DIODE FORWARD CHARACTERISTICS (TYPICAL)




ON-STATE RESISTANCE VS. CHANNEL TEMPERATURE (TYPICAL)



THRESHOLD VOLTAGE VS. CHANNEL TEMPERATURE (TYPICAL)



BREAKDOWN VOLTAGE VS. CHANNEL TEMPERATURE (TYPICAL)



TRANSIENT THERMAL IMPEDANCE CHARACTERISTICS

