

## Features



- Screw thread coupling
- One-piece Tunable connector (adjustable to 6 positions)
- "N" keyed type
- Pull proof
- "PC" pre-radius (20mm) zirconia ceramic ferrule
- "APC" pencil zirconia ceramic ferrule
- Secure crimping (double ferrule)
- Secure bonding
- Cable range : 0.9 to 3mm, tight or semi-loose structure
- Boots color code : yellow boot in singlemode PC  
Black boot in multimode PC


Cable diameter (mm)	Packaging	PC125 Singlemode	PC126 Singlemode	PC128 multimode	PC230 multimode	APC125 singlemode	APC126 Singlemode
Level "zero" (1)	100	F 729 101 000	F 729 102 000	F 729 103 000	-	F 729 111 000	F 729 112 000
0.9 ( Buffer)	1	F 729 001 100	F 729 002 100	F 729 003 100	-	F 729 011 100	F 729 012 100
0.9 ( Buffer)	100	F 729 101 100	F 729 102 100	F 729 103 100	-	F 729 111 100	F 729 112 100
0.6/1 (tube)	1	F 729 001 200	F 729 002 200	-	-	-	-
0.6/1 (tube)	100	F 729 101 200	F 729 102 200	-	-	-	-
0.8/1.6 (tube)	1	F 729 001 300	F 729 002 300	-	-	-	-
0.8/1.6 (tube)	100	F 729 101 300	F 729 102 300	-	-	-	-
1.6	1	F 729 001 400	F 729 002 400	F 729 003 400	-	F 729 011 400	F 729 012 400
1.6	100	F 729 101 400	F 729 102 400	F 729 103 400	-	F 729 111 400	F 729 112 400
2	1	F 729 001 500	F 729 002 500	F 729 003 500	-	F 729 011 500	F 729 012 500
2	100	F 729 101 500	F 729 102 500	F 729 103 500	-	F 729 111 500	F 729 112 500
2.4	1	F 729 001 600	F 729 002 600	F 729 003 600	-	F 729 011 600	F 729 012 600
2.4	100	F 729 101 600	F 729 102 600	F 729 103 600	-	F 729 111 600	F 729 112 600
3	1	F 729 001 700	F 729 002 700	F 729 003 700	F 729 005 700	F 729 011 700	F 729 012 700
3	100	F 729 101 700	F 729 102 700	F 729 103 700	F 729 105 700	F 729 111 700	F 729 112 700

(1) the level "zero" is supplied without boots or crimp sleeves and allows the user to manage his cable diameters, colour of boots, etc... According to the situation.

All accessories (boots, crimp sleeves, etc...) can be ordered separately. These accessories are common to SC and FC. See page 31 for part numbers.

### Connector body

PC125 pigtailed mode  
PC125 single mode  
PC128 multimode




[inches]

1.531 inches  
27mm (1.063 inches)

### Connector body

APC125 pigtailed mode  
APC125 single mode



1.531 inches  
27mm (1.063 inches)

Cable diameter mm	Boots / Accessories	Mechanical dimensions Mm/Inch
0.9 mm		
0.6/1 mm		
0.8/1.6 mm		
2 - 2.4 - 3 mm		

Inside diameter of crimp rings varies according to cable diameter (2, 2.4 or 3 mm).

Rear part of the boot varies according to cable diameter (0.6/1) - (0.8/1.6 ; 2 - 2.4) - (3 mm)