


BNC 50 Ohm Termination

Description

BNC 50 Ohm Termination Plug - Straight




Ordering Data

BNC 50 Ohm Termination Plug - Straight

Part Number	Resistor ±5%		Dimension						Finish	Chain Length	
			A		B		C				
	Ohm	Watt	mm	in.	mm	in.	mm	in.		mm	in.
28PO100-1	100	0.5	30.16	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-2	51	0.5	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-3	75	0.5	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-4	91	0.5	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-5	510	0.5	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-6	1000	0.5	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-7	150	0.5	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO100-8	51	1.0	30.18	1.188	12.70	0.500	3.66	0.144	Silver	88.90	3.500
28PO101-2	51	0.5	28.58	1.125	11.11	0.438	3.66	0.144	Silver	88.90	3.500
28PO101-3	75	0.5	28.58	1.125	11.11	0.438	3.66	0.144	Silver	88.90	3.500
28PO101-4	91	0.5	28.58	1.125	11.11	0.438	3.66	0.144	Silver	88.90	3.500
28PO102-1	51	0.5	28.58	1.125	11.11	0.438	No Chain		Nickel	N/A	
28PO102-4	100	0.5	28.58	1.125	11.11	0.438	No Chain		Silver	N/A	
28PO107-1	51	2.0	38.50	1.516	14.29	0.563	3.66	0.144	Nickel	88.90	3.500

Description

BNC 50 Ohm Termination Plug -
Single Hole Mount Straight



Ordering Data

BNC 50 Ohm Termination Plug - Single Hole Mount Straight

Part Number	Cable RG-/U	Dimension						Finish	Mtg. Hole
		A		B		C			
		mm	in.	mm	in.	mm	in.		
28TS102-1	55, 58, 223	22.23	0.875	12.70	0.500	7.94	0.313	Silver	C3
28TS105-1	59, 62, 71	22.23	0.875	12.70	0.500	7.94	0.313	Silver	C3