



- △ PHENOLIC, BLACK.
- △ DIALLYL PHTHALATE, BLUE.
- △ EACH POST WILL ACCEPT (SEE TABLE) TERMINATIONS OF #24 AWG MAX WIRE.
- △ 0.76um[.000030] MIN GOLD ON MATING END FOR A LENGTH OF 5.08[.200] MIN. GOLD FLASH ON THE REMAINDER OVER 0.76um [.000030] MIN NICKEL.
- △ 2.54um [.000100] MIN TIN-LEAD OVER 2.54um [.000100] MIN NICKEL.
- △ POSTS ARE SEMI-AUTOMATICALLY WIRABLE.
- △ 5.54[.218] IS REQUIRED WHEN JACKSCREWS ARE USED.
- △ 2.54um [.000100] MIN TIN OVER 2.54um [.000100] MIN NICKEL.
- △ 2.54um [.000100] MIN TIN OVER 1.27um [.000050] MIN NICKEL.

△	△	△	1	6.63 [.261]	6-205505-4
△	△	△	1	6.63 [.261]	6-205505-3
△	△	△	3	16.74 [.659]	6-205505-2
△	△	△	3	16.74 [.659]	4-205505-6
△	△	△	1	6.63 [.261]	3-205505-3
△	△	△	1	6.63 [.261]	3-205505-1
△	△	△	3	16.74 [.659]	205505-1
POST FINISH	CONTACT FINISH	HOUSING	NO OF TERM	A	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT. DWN: C. OBERMAN 13 OCT 97  
 CHK: R. STONE 30 SEP 97  
 APD: G. STEINHAUER 31 OCT 97

tyco  
 Electronics  
 Tyco Electronics Corporation  
 Harrisburg, Pa 17105-3608

NAME: CONNECTOR ASSEMBLY, POSTED SOCKET, 34 POSITION, M SERIES

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 205505 RESTRICTED TO: -  
 WEIGHT: -  
 MATERIAL: SEE CALLOUT FINISH: SEE CALLOUT CUSTOMER DRAWING SCALE: 2:1 SHEET: 1 OF 1 REV: V