

UniCam® Connector, ST® compatible, Organiser Pack

single-mode (OS2)

CORNING

Corning UniCam® high-performance connectors offer best-in-class optical performance in a fast, easy field-termination solution. These high-precision zirconia ceramic ferrule connectors assured exceptional insertion loss – 0.1 dB typical/0.5 dB maximum per connector pair for multimode, 0.2 dB typical/0.5 dB maximum per connector pair for single-mode. Installation of an LC, SC or ST® compatible connector can be accomplished in about 50 seconds to one minute with the UniCam high-performance tool kit.

The lightweight, handheld installation tool and high-performance precision cleaver virtually eliminate human variability during installation, ensuring terminations are right the first time, every time. This kit was designed with consideration for network installers, from the cleaver, with its intuitive, hand-held precision design and dual-clamp precision hold, to the installation tool, with its immediate go/no-go feedback signal indicating proper mating of the field fibre to the fibre stub. Installation is as easy as strip, clean, cleave, cam and crimp, with exceptional optical performance assured. Every UniCam® connector is assured to meet the published specification at the time of installation or Corning will replace it.

Organizer packs include 900 µm boots only.



Features and Benefits

Performance guarantee

100 percent yield guarantee

Factory-polished end face

Consistent optical performance

Fast termination and no consumables

Low installation cost

Minimum insertion loss

Optimum optical performance

Standards

Approvals and Listings

Compliant with EIA/TIA
568-B.3

Intermateability

Connectors are FOCIS
compliant with TIA/EIA 604-
3 and IEC61754-4

UniCam[®] Connector, ST[®] compatible, Organiser Pack

single-mode (OS2)

CORNING

Specifications

General Specifications	
Technology	No-epoxy/no-polish
Keyed	No
Product type	Field-Installable Connectors
Corning Logo	Yes
Packaging	Organiser Pack
Fibre Category	single-mode (OS2)

Temperature Range	
Operation	0 °C to 60 °C (32 °F to 140 °F)

Design - Connector	
Connector Type	ST [®] Compatible
Ferrule Material	Ceramic
Housing material	Composite
Housing Colour	Amber
Boot colour	Blue

Mechanical Specifications - Connector	
Durability	≤ 0.2 dB change by 500 rematings, FOTP-21
Nominal fibre outer diameter	125 µm
Tensile strength jacketed cable	44 N, change ≤ 0.2 dB, FOTP-6 (11 lb, change ≤ 0.2 dB, FOTP-6)
Tensile strength 900 µm cable	4.9 N, change ≤ 0.2 dB, FOTP-6 (1.1 lb, change ≤ 0.2 dB, FOTP-6)

Optical Specifications - Connector	
Insertion loss, typical	0.2 dB
Insertion Loss, Maximum	0.5 dB
Reflectance	≤ -55 dB
Polish	UPC

UniCam[®] Connector, ST[®] compatible, Organiser Pack

single-mode (OS2)



Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	95-200-51-Z
Product Description	UniCam [®] High-Performance Connector, ST [®] compatible, single-mode (OS2), ceramic ferrule, logo, organiser pack, amber housing, blue boot
EAN Code	4056418196251

Shipping Information

Units Per Delivery	25/1
Package Contents	25 connectors, 25 boots (900 µm)

