



Quad 3 Input NOR Gate
320 ps Gate Delay
10G PicoLogic™ Family

DISTINCTIVE CAPABILITIES

- 320 ps max. propagation delay
- Output rise and fall times of 150 ps
- 0°C to +85°C operating temperature range
- 10G PicoLogic compatible inputs and outputs
- VBB reference voltage for improved threshold tracking over temperature and power supply variation
- On-chip VBBS threshold reference voltage supply
- Supports a wide range of load resistor and termination voltage combinations
- Wire-OR output capability
- Available in 40 pin C-leaded or leadless chip carrier or die form
- Packages contain internal decoupling capacitors for optimum high frequency performance

APPLICATIONS


- Logic functions
- Data distribution
- High speed TTL/CMOS to10G/ECL and 10G to TTL/CMOS translation ability
- Precision gating/strobing
- Digital multiplexing

FUNCTIONAL DESCRIPTION

The 10G000A is an ultra fast quad 3 input NOR gate featuring a maximum propagation delay of 320 ps for packaged parts. It offers a typical speed four times faster than equivalent ECL NOR gates. The 10G000A is ideally suited for use in high performance systems requiring improved throughput, reduced signal skew and increased timing margin. It can also drive and be driven from CMOS and TTL gates, providing the user a high speed TTL/CMOS to10G/ECL translation capability.

For compatibility with other high speed logic families, the 10G000A features the PicoLogic™ family standard VBB input. This input allows the 10G000A's threshold voltage to be controlled by the driving logic family. Therefore, mismatches in threshold level due to temperature and powersupply vaiations can be compensated, providing high system noise immunity. An on-chip threshold voltage output (pin VBBS) is also provided. VBBS must be strapped to the VBB input when PicoLogic™ is used to drive the 10G000A. The 10G000A has input clamps VICH and VICL. When connected to -1.3V, these internally truncate an overdriven sine wave input signal to a square wave, thus allowing inputs to be driven with faster rise and fall times. When not used, the input clamps should be connected to VICL = VSS and VICH = VDDO for transient protection.


BLOCK DIAGRAM



10G000A ORDERING INFORMATION

| PACKAGE TYPE | DELAY (Max @ 25°C) | |
|-------------------|----------------------|------------|
| | 320 ps | 390 ps |
| 40Pin C-Leaded CC | 10G000A-C | 10G000A-4C |
| 40Pin Leadless CC | 10G000A-L | 10G000A-4L |
| Die | | 10G000A-4X |



| FUNCTIONAL DESCRIPTION (Continued) | PIN DESCRIPTIONS | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|--------|--------|--|--------|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| <p>A major design goal of the PicoLogic™ family is to provide full interface capability to other logic families without sacrificing noise immunity. Since each family exhibits differing input threshold sensitivity to temperature and power supply variations, it is necessary to "tell" the PicoLogic™ device which family it is interfacing to. This can easily be accomplished via the VBB input pin. A nominal -1.3V reference voltage is applied to the VBB pin to cause the PicoLogic™ threshold to equal and track the threshold of the interfacing logic family.</p> <p>When the 10G000A is interfaced with other PicoLogic™ parts, VBB may be strapped to the VBBS output pin. The internal VBBS circuit generates a nominal -1.3V reference output with only a 17% VSS sensitivity. It thus provides a convenient reference supply which can be used over the commercial temperature range of 0°C to + 85°C for a GaAs to GaAs interface.</p> <p>If VBBS is not supplied by the other logic family, it may be generated by connecting an inverting device output to its input as illustrated below.</p> | <p>D1-4 Data inputs OUT1-4 Outputs VDDO Output driver ground (0V) VDDL Internal logic ground (0V) VSS -3.4V power supply VEE -5.2V power supply VTTC VDDO internal decoupling capacitor return. VTTC is brought into the 10G000A package as the AC return lead for the internal VDDO output driver decoupling capacitor. It is not brought onto the 10G000A die. VTTC is typically equal to VTT (nominally -2.0V). VDCH Output driver clamp supply. When VDCH is connected to VTT = -2.0V the output driver high level is limited to approximately -0.6V, thus providing ECL output compatibility. When not used, VDCH should be connected to VDDO. VICH,VICL Input protection clamp supply. When connected to -1.3V, these allow an over-driven sine wave input signal to be truncated to a square wave, thus allowing inputs to be driven with faster rise and fall times. When not used, the input clamps should be connected to VICL =VSS and VICH =VDDO for transient protection. VBB GaAs threshold reference input voltage. Allows direct tracking of another family's reference voltage. Connect to VBBS for PicoLogic™ interface. When interfacing with ECL, connect to the reference voltage supply (VBB). This pin may not be left unconnected. VBBS GaAs threshold reference voltage. Connect to VBB when interfacing with PicoLogic™.</p> | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Generating the Switching Threshold (VBB) Reference Level from Interfacing Logic.</p>  | <p style="text-align: center;">TRUTH TABLE</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="3" style="text-align: center;">INPUTS</th> <th rowspan="2" style="text-align: center;">OUTPUT</th> </tr> <tr> <th style="text-align: center;">A</th> <th style="text-align: center;">B</th> <th style="text-align: center;">C</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">H</td> <td style="text-align: center;">X</td> <td style="text-align: center;">X</td> <td style="text-align: center;">L</td> </tr> <tr> <td style="text-align: center;">X</td> <td style="text-align: center;">H</td> <td style="text-align: center;">X</td> <td style="text-align: center;">L</td> </tr> <tr> <td style="text-align: center;">X</td> <td style="text-align: center;">X</td> <td style="text-align: center;">H</td> <td style="text-align: center;">L</td> </tr> <tr> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">L</td> <td style="text-align: center;">H</td> </tr> </tbody> </table> <p style="text-align: center;">X = Don't care input</p> | INPUTS | | | OUTPUT | A | B | C | H | X | X | L | X | H | X | L | X | X | H | L | L | L | L | H |
| INPUTS | | | OUTPUT | | | | | | | | | | | | | | | | | | | | | |
| A | B | C | | | | | | | | | | | | | | | | | | | | | | |
| H | X | X | L | | | | | | | | | | | | | | | | | | | | | |
| X | H | X | L | | | | | | | | | | | | | | | | | | | | | |
| X | X | H | L | | | | | | | | | | | | | | | | | | | | | |
| L | L | L | H | | | | | | | | | | | | | | | | | | | | | |



DC CHARACTERISTICS
 Tc = 0 °C to + 85 °C, VSS = -3.5V to -3.3V, VEE = -5.5V to -5.1V, VDDL=VDDO = 0V, unless otherwise indicated.

| SYMBOL | PARAMETER | MIN | TYP | MAX | UNITS | TEST CONDITIONS |
|--------|----------------------|------|-----|--------|-------|-----------------------|
| VIH | Input Voltage High | -0.7 | | VDDL | V | VIN: -0.7 V to -1.8 V |
| VOH | Output Voltage High | -0.7 | | | V | |
| VIL | Input Voltage Low | VSS | | -1.8 V | V | |
| IIN | Input Current | -100 | 120 | 400 | µA | |
| ISS | Power Supply Current | | 110 | 180 | mA | |
| IEE | Power Supply Current | | 25 | 45 | mA | |
| PD | Power Dissipation | | 500 | 875 | mW | |

Note: The remaining DC Characteristics are specified in the 10G PicoLogic™ Family Electrical Characteristics Table at the beginning of this section. This table notes parameter deviations to Family Characteristics and provides specific supplementary characteristics only.

AC CHARACTERISTICS (Note 1,3)

VSS = -3.5V to -3.3V, VEE = -5.5V to -5.1V, VDDL=VDDO = 0V, unless otherwise indicated.

10G000A

| SYMBOL | PARAMETER | Tc = 0°C | | Tc = +25°C | | | Tc = +85°C | | UNITS | NOTES |
|--------|--------------------------|----------|-----|------------|-----|-----|------------|-----|-------|-------|
| | | MIN | MAX | MIN | TYP | MAX | MIN | MAX | | |
| T1 | Prop. Delay, Low to High | 235 | 330 | 230 | 300 | 320 | 245 | 350 | ps | |
| T2 | Prop. Delay, High to Low | 235 | 330 | 230 | 300 | 320 | 245 | 350 | ps | |
| T3 | Output Rise Time | | 175 | | 150 | 175 | | 190 | ps | 2 |
| T4 | Output Fall Time | | 175 | | 150 | 175 | | 190 | ps | 2 |

10G000A-4

| SYMBOL | PARAMETER | Tc = 0°C | | Tc = +25°C | | | Tc = +85°C | | UNITS | NOTES |
|--------|--------------------------|----------|-----|------------|-----|-----|------------|-----|-------|-------|
| | | MIN | MAX | MIN | TYP | MAX | MIN | MAX | | |
| T1 | Prop. Delay, Low to High | 265 | 390 | 265 | 360 | 390 | 275 | 410 | ps | |
| T2 | Prop. Delay, High to Low | 265 | 390 | 265 | 360 | 390 | 275 | 410 | ps | |
| T3 | Output Rise Time | | 215 | | 190 | 215 | | 230 | ps | 2 |
| T4 | Output Fall Time | | 215 | | 190 | 215 | | 230 | ps | 2 |

Note 1. Test conditions (unless otherwise indicated) :



- | | | |
|----------------------|--------------|-------------|
| VBB = -1.3 V | VICH = 0V | VIH = -0.7V |
| VTT = -2.0V | VICL = VSS | VIL = -1.8V |
| VTTc = VTT | VDCH = -2.0V | VOH = -0.7V |
| RLOAD = 50Ω to -2.0V | | VOL = -1.8V |

Input signal rise and fall time ≤ 150 ps





- Rise and fall times are measured between 20% and 80% points.
- All values of parameters T1 and T2 are 30 ps less for the "L36" and "F" packages.



TYPICAL PERFORMANCE CHARACTERISTICS




VBB = -1.3V. The VOH and VOL curves result when the inputs are driven from -0.6V to -1.8V. The VIH and VIL curves shown result in output levels from -0.6V to -1.8V.






SWITCHING WAVEFORMS



PIN FUNCTIONS - PACKAGE TYPES "L" AND "C"






**24 PIN HYBRID
18 PIN PACKAGE**


T-90-20

24 PIN HYBRID PACKAGE

Type H




**18 PIN LEADLESS CHIP CARRIER
TYPE L1**






**36 PIN LEADLESS CHIP CARRIER
TYPE L36**



NOTES:


- 1) The package bottom thermal vias, top lid surface and 4 metallized corner castellations (when present) are all at V_{SS} potential.
- 2) All dimensions in inches.
- 3) Pin #1 identifier may be an elongated pad or small, square gray marker.

**36 I/O LEAD FLATPACK
TYPE F**




11

40 PIN LEADLESS CHIP CARRIER
TYPE L




40 PIN LEADED CHIP CARRIER
TYPE C



NOTES:

- (1) Footprint is JEDEC standard outline.
- (2) Top surface vias (for terminating resistors and decoupling capacitors) are not available on pins 3, 4, 17, 18, 23, 24, 37 and 38.
- (3) Top surface metal (not including vias) and pins 3 and 23 are fixed at VTT potential.
- (4) Recommended top surface chip resistors are 0.040 long by 0.020 wide by 0.010 thick typ, 100 mw min. nominal power rating (Mini-Systems MSR-21 or equivalent).
- (5) Recommended top surface chip capacitors are 0.040 long by 0.030 wide by 0.020 thick typ, 25V VDCW, 1000 pf. min. (Johnson R02 case or equivalent).
- (6) Recommended heatsinks are GBL P/Ns 90GHS-40-A and 90GHS-40-B.
- (7) Thermally conductive, electrically non-conductive epoxy is recommended for heatsink attachment (Ablestick 789-4 or 501K, or Thermalloy Thermalbond™ or equivalent).
- (8) L40 and C40 packages are dimensionally identical except for contact finger width.


| TOP SURFACE LEGEND: | |
|--------------------------|---|
| Metalized Ceramic..... | ■ |
| Screened Dielectric..... | ▨ |
| Bare Ceramic..... | □ |






68 & 132 PIN
PACKAGES
T-90-20

68 PIN LEADED CHIP CARRIER
TYPE C1



- (1) All dimensions in inches.
- (2) a. C1A: Package lid, top, and pins 4, 9, 14, 21, 26, 31, 38, 43, 48, 55, 60, 65 are at common potential (system ground).
- b. C1B: Package lid and pins 4, 9, 14, 21, 26, 31, 38, 43, 48, 55, 60, 65 are at common potential (system ground).

132 PIN LEADED CHIP CARRIER
TYPE C3



11