

SILICON TRANSISTORS

DEVICE TYPE NO.	POLARITY	MAXIMUM RATINGS					ELECTRICAL CHARACTERISTICS				CASE
		P _d @ T _c =25°C WATTS	I _c AMPS	BV _{CB0}	BV _{CE}	BV _{EB0}	h _{FE} MIN.	I _c AMPS	V _{CE}	f MHZ *KHZ	
2N6676	NPN	175	15.0	450	300	8	8	15.0	3	15	T03
2N6677	NPN	175	15.0	550	350	8	8	15.0	3	15	T03
2N6678	NPN	175	15.0	650	400	8	8	15.0	3	15	T03
2N6738	NPN	100	8.00	450	300	8	10	5.00	3	15	TO220
2N6739	NPN	100	8.00	550	350	8	10	5.00	3	15	TO220
2N6740	NPN	100	8.00	650	400	8	10	5.00	3	15	TO220
2N6751	NPN	150	10.0	800	400	8	8	5.00	3	15	T03
2N6752	NPN	150	10.0	850	450	8	8	5.00	3	15	T03
2N6753	NPN	150	10.0	900	500	8	8	5.00	3	15	T03
2N6754	NPN	150	10.0	1000	500	8	8	5.00	3	15	T03
2N6834	NPN	125	5.00	850	450	6	7.5	3.00	5	15	T03
2N6835	NPN	150	8.00	850	450	6	7.5	5.00	5	10	T03
2N6836	NPN	175	15.0	850	450	6	7.5	10.0	5	10	T03
40080	NPN	.500	.250	60	30	4	40	.10	5	200	TO39
40081	NPN	2.00	.250	60	60	4	40	.20	5	200	TO39
40084	NPN	.500	1.00	60	40	5	5	50.0	10	100	TO18
40231	NPN	.500	.100	18	18	5	55	.002	10	60	TO18
40232	NPN	.500	.100	18	18	5	90	.002	10	60	TO18
40232	NPN	.500	.100	18	18	5	90	.002	10	60	TO18
40234	NPN	.500	.100	18	18	5	35	.002	10	60	TO18
40235	NPN	.180	.050	45	30	4.5	40	.001	6	800	TO72
40236	NPN	.180	.050	45	30	4.5	40	.001	6	800	TO72
40237	NPN	.180	.050	45	30	4.5	27	.001	6	800	TO72
40238	NPN	.180	.050	45	30	4.5	40	.001	6	800	TO72
40239	NPN	.180	.050	45	30	4.5	27	.001	6	800	TO72
40240	NPN	.180	.050	45	30	4.5	27	.001	6	800	TO72
40242	NPN	.180	.050	45	45	4.5	40	.001	6	800	TO72
40243	NPN	.180	.050	45	45	4.5	40	.001	6	800	TO72
40244	NPN	.180	.050	45	45	4.5	27	.001	6	800	TO72
40245	NPN	.180	.050	45	45	4.5	70	.001	6	800	TO72
40246	NPN	.180	.050	45	45	4.5	27	.001	6	800	TO72
40250	NPN	29.0	4.00	50	40	5	25	1.50	4	1	TO66
40251	NPN	117	15.0	50	40	5	15	1.50	4	1	T03
40280	NPN	7.00	.500	36	18	4	15	.100	10	550	TO39
40309	NPN	1.00	.700	25	18	2.5	70	.050	4	100	TO39
40310	NPN	29.0	4.00	40	35	2.5	20	1.00	2	*750	TO66
40311	NPN	1.00	.700	45	30	2.5	70	.050	4	100	TO39
40312	NPN	29.0	4.00	70	60	2.5	20	1.00	2	*750	TO66
40314	NPN	1.00	.700	45	40	2.5	70	.050	4	100	TO39
40315	NPN	1.00	.700	40	35	2.5	70	.050	4	100	TO39
40319	PNP	1.00	.700	45	40	2.5	35	.050	4	100	TO39
40320	PNP	1.00	.700	45	40	2.5	40	.010	4	40	TO39
40321	NPN	1.00	1.00	300	300	5	25	.020	10	5	TO39
40323	NPN	1.00	.700	20	18	2.5	70	.050	4	100	TO39
40324	NPN	29.0	4.00	40	35	4	20	1.00	2	*750	TO66
40325	NPN	117	15.0	35	35	5	12	8.00	4	*200	T03
40326	NPN	1.00	.700	50	40	2.5	40	.010	10	40	TO39
40327	NPN	1.00	1.00	300	200	5	40	.020	10	5	TO39
40346	NPN	1.00	1.00		175		25	.010	10	10	TO39
40347	NPN	1.00	1.50	60	40	7	25	.450	4	40	TO39
40348	NPN	1.00	1.50	90	65	7	30	.300	4	40	TO39
40349	NPN	1.00	1.50	160	140	7	30	.150	4	40	TO39
40360	NPN	1.00	.700	80	70	4	40	.010	4	100	TO39
40361	NPN	1.00	.700	80	70	4	70	.050	4	100	TO39
40362	PNP	5.00	.700	80	70	4	35	.050	4	100	TO39
40363	NPN	115	17.0	75	70	4	20	4.00	4	*700	T03
40364	NPN	35.0	7.00		60		4	.500	5	15	TO66
40385	NPN	1.00	1.00	450	350	7	40	.020	10	15	TO66
40399	NPN	.500	.200	18	18	7	165	10.0	10	50	TO18
40400	NPN	.500	.200	18	18	7	75	10.0	10	50	TO18
40406	PNP	1.00	.700	60	50	4	30	.0001	10	100	TO39
40407	NPN	1.00	.700	60	50	4	40	.001	10	100	TO39

