



SPECIFICATION

Current Rating: 1A
 Insulation Resistance : 500 Megohms/Min.
 Withstanding Voltage : 500V AC/Min.
 Contact Resistance : 35 Milliohms Max.
 Temperature Range : -55°C To +105°C
 Housing And Cover : Plastic Thermoplastic
 P.B.T UL 94V-0
 Contact: Phosphor Bronze Gold Selective Plated Over Tin
 Shell : Steel, Nickel Or Tin Plated Over Copper
 Bracket: Steel, Nickel Plated Over Copper
 Boardlock : Brass Tin Plated Over Copper

| Circuits | A | B | C | D | E | F |
|----------|-------|-------|-------|-------|-------|-------|
| 14 | 29.57 | 23.64 | 12.63 | 23.64 | 7.62 | 17.02 |
| 20 | 33.38 | 27.45 | 16.44 | 27.45 | 11.43 | 20.83 |
| 26 | 37.19 | 31.26 | 20.25 | 31.26 | 15.24 | 24.64 |
| 36 | 43.54 | 37.61 | 26.60 | 37.61 | 21.59 | 30.99 |
| 50 | 52.43 | 46.50 | 35.49 | 46.50 | 30.48 | 39.88 |

AUK A NUMBER OF AUK GROUP
太聯事業股份有限公司
 AUK CONTRACTORS CO., LTD.

DRAWING No.
 HPC020SR

APPROVED BY MEI
 CHECKED BY RAN
 DRAWING BY HZF

UNLESS OTHERWISE SPECIFIED
 TOLERANCES ARE
 .X ±0.38
 .XX ±0.25
 AWG.

SCALE NONE

REV. A

UNIT mm

AREA REVISIONS CHK DATE