



NOTES:

1. DESIGN AND INTERFACE PER I. D. S. -33.
2. FOR USE WITH (M17/152) RG-316 D/S CABLE.
3. CRIMP WITH .151HEX DIE (M22520/5-37).
4. ORIENTATE PART IN CRIMP TOOL SO THAT A HEX FLAT WILL BE PARALLEL TO THE MATING SURFACE.
5. CAP AND FERRULE SHIPPED LOOSE.

				<p>PALCO CONNECTOR</p> <p>22 GREAT HILL RD., NAUGATUCK, CT 06770</p> <p>UNLESS OTHERWISE SPECIFIED, PALCO WORKMANSHIP STANDARDS APPLY</p> <p>TOLERANCES IN DECIMALS: XX ± .01 .XXX ± .005 ANGLES ± 1/2°</p> <p>DIMENSIONS IN INCHES OR (METRIC) DO NOT SCALE PRINTS</p>	DRAWN YS	CHECKED HN	ENGINEER JEM	APPROVED HN	FSCM 58167
G	PER ECN 4748	10/26/98	HN		DESCRIPTION RIGHT ANGLE PMMX PLUG, CRIMP TYPE	DATE	DRAWING NO.		PLATING OPT.
F	PER ECN 3572	09/30/96	HN			06/15/94	33-2800-2670		A
E	PER ECN 3343	02/20/96	HN						
REV.	DESCRIPTION	DATE	APPR.		MAT. CATALOG ITEM				