



Package	Length L
UM-1J	8.00 max
UM-5J	6.00 max

90° cranked leads are available as an option to save approx 1mm in overall length. Contact our sales office for more details.

## Features

- ▶ Ideal for custom frequencies & specifications
- ▶ Wide frequency range
- ▶ Tight specifications available
- ▶ Fundamental mode up to 55.0MHz

## ESR Values

The table shows the maximum ESR values in ohms for each package across the available frequency range.

Frequency	Mode	UM-1J	UM-5J
3.5 ~ 4.99	Fundamental	200	-
5.0 ~ 5.99	Fundamental	150	-
6.0 ~ 6.99	Fundamental	120	-
7.0 ~ 7.99	Fundamental	100	-
8.0 ~ 9.99	Fundamental	90	-
10.0 ~ 15.9	Fundamental	40	60
16.0 ~ 55.0	Fundamental	30	40
30.0 ~ 49.9	3rd overtone	45	50
50.0 ~ 100	3rd overtone	60	60
60.0 ~ 150	5th overtone	90	120
130 ~ 300	7th overtone	150	150

## Specifications

**UM-1J: 8.0mm maximum body length**

**UM-5J: 6.0mm maximum body length**

Parameters	Product		Option Code
	UM-1J	UM-5J	
Package:	UM-1J UM-5J	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Frequency range:	3.579 ~ 300MHz 10.0 ~ 300MHz	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Calibration tolerance:	±5ppm ±7.5ppm ±10ppm ±20ppm ±30ppm Other values (±3ppm ~ ±100ppm)	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	L M 1 2 3 specify
Temperature stability:	±5ppm ±7.5ppm ±10ppm ±20ppm ±30ppm Other values (±3ppm ~ ±100ppm)	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>	L M 1 2 3 specify
Operating temperature range:	0 to +50°C -10 to +60°C -20 to +70°C -30 to +80°C -40 to +85°C Other values	<input type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	0 1 2 3 4 specify
Circuit condition:	12pF 16pF 20pF 30pF Series resonant Other values	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	B D F J S specify
Oscillation mode:	Fundamental 3rd overtone 5th overtone 7th overtone	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	F 3 5 7
Static capacitance (C0):	7pF max	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Equivalent series resistance (max):	see table	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Ageing:	±3ppm max first year	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Test drive level:	100µW	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	
Soldering conditions:	260°C, 10sec max x 2	<input checked="" type="checkbox"/> <input checked="" type="checkbox"/>	

■ Standard. □ Optional - Please specify required code(s) when ordering

## Ordering Information

Product name + option codes + frequency  
eg: **UM-1J/231JF 16.0MHz** 20/30/10/30-F

- ◆ Available on T&R - 1k pcs per reel.
- ◆ Refer to our website for T&R and soldering details.
- ◆ Some combinations of stability and temperature range may not be available. Please check with us before ordering.