

# FC Connectors

FC Type Fiber Optic connectors

## Connector SNP-8 Series



### Angle PC Application Easy Assembly Singlemode

- Housing designed for Angle PC application
- Uses a zirconia ferrule having a conical tip
- Angled endface shape for easier polishing
- Keying width: 2.14 + 0/-0.05 mm (N type)
- Combined with SNA-1/3 (adapter) provides low insertion loss and ultra high return loss

### ORDERING INFORMATION

Model Number	Type Number
SNP-8	8 3 1 2 5 1 B 3 0 2

Boot Color	
0	Black
8	Green

Boot I.D. (mm)	
1	0.9 (flame-resistant rubber)
3	3.0 (plastic)
6	2.0 (plastic)
9	0.9 (plastic)

Ferrule I.D. (μm)	
ø 125	ø 126

Specifications	
02	N type

Package	
1	Individual
3	Bulk

Cap	
0	No Cap
8	Green PVC
B	Green Ferrule

Marking of Boot		
		Applicable Boot (mm)
0	Without	0.9 (flame-resistant rubber)
1	SII Marking	0.9~3.0 (plastic)

Easy Assembly

## Adapter SAA-1 Series



### PC Application Singlemode

- Precision sleeve (phosphor bronze/zirconia)
- Excellent detachability

### ORDERING INFORMATION

Model Number	Type Number
SAA-1	1 2 2 0 0

Slit Sleeve	
1	Phosphor Bronze
2	Zirconia

Marking	
1	Without
2	SAA-1 JAPAN SII

(Required)

Cap	
1	White (plastic)
2	Red (synthetic rubber)

High Reliability