

| ISS |  | ZONE |  | REVISIONS |  | DESCRIPTION\PER REQUEST\DATE |  |
|-----|--|------|--|-----------|--|------------------------------|--|
|     |  |      |  |           |  |                              |  |

  

ROLLING  
FLARING

④ ③ ②

∅2.1  
∅1.1

29.4

∅3.1  
∅4.7

RECOMMENDED  
CABLE STRIPPING DIM'S

6 7.9 3.2

  

5/8-24UNEF-2B

∅18.2

10.5

∅14

∅6.3

∅5.7

7.3

  

1. CRIMPED CONTACT PIN  
HEX CRIMP SIZE .068"

  

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- BRASS PER QQ-B-626
- NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- SILVER PL. 200 MIN. THICK OVER COPPER STRIKE
- PHENOLIC, YELLOW PANTONE 110C

|  |  |  |  |                            |          |
|--|--|--|--|----------------------------|----------|
| DIMENSIONS ARE IN MILLIMETERS  |  |  |  | PART NO. U1161A1-NPHS-1-50 |          |
| UNLESS OTHERWISE SPECIFIED TOLERANCES<br>0.5-6 = ±0.2<br>6-30 = ±0.4<br>30-120 = ±0.6<br>120-315 = ±1<br>315-1000 = ±1.6<br>1000-2000 = ±2.4 |  |  |  | APPROVED                   | DATE     |
|  |  |  |  | CHECKED                    | DATE     |
|  |  |  |  | DRAWN                      | DATE     |
|  |  |  |  | SCALE                      | FILE NO. |

|  |  |
|--|--|
| <b>Amphenol</b>                        |  |
| TITLE<br>UHF FCP PLUG                  |  |
| DRAWING NO.<br>KJ-U1161A1-NPHS-58CU-50 |  |
| ITEM NO.                               |  |

| NO. | DESCRIPTION | MATERIAL | FINISH | Q'TY | DRAWING NO.   |
|-----|-------------|----------|--------|------|---------------|
| 5   | FERRULE     | NOTE 1   | NOTE 2 | 1    | U5010-5       |
| 4   | CONTACT PIN | NOTE 1   | NOTE 3 | 1    | U5000-4-21/11 |
| 3   | INSULATOR   | NOTE 4   | NOTE 4 | 1    | U5290-3PHE-50 |
| 2   | BODY        | NOTE 1   | NOTE 2 | 1    | U5010-2       |
| 1   | SHELL       | NOTE 1   | NOTE 2 | 1    | U5010-1       |