



SLIDE SWITCHES



✓ Active

↓ **PRODUCT DRAWING**
English

TE CONNECTIVITY (TE)

MSSA2350RG=SLIDE 2 POLE/ 3 POS

[Alcoswitch](#) | [MSSA](#)

MSSA2350RG

TE Internal Number: 5-1437580-6

5 of 6 EU RoHS/ELV Compliant

[Find Compliant Alternatives](#)

Configuration (Pole-Throw) **Double Pole - Three Throw**

Mounting Angle **Vertical**

Contact Base Material **Copper Alloy**

Number of Actuators **Single**

Number of Positions **3**

Product Drawings

[SLIDE SWITCH](#)

PDF **(TIFF AVAILABLE)**
English

[SLIDE SWITCH](#)

PDF **(TIFF AVAILABLE)**
English

Catalog Pages/Data Sheets

[SWITCHES_CORE_PROGRAM_CATALOG](#)

PDF
English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features

Actuator Style	Extended, Side
Threaded Case	Without
Terminal Configuration	Standard
Product Type	Switch
Grade	Instrumentation
Switch Type	Slide

Configuration Features

Configuration (Pole-Throw)	Double Pole - Three Throw
Number of Actuators	Single
Number of Positions	3

Body Features

Actuator Material	Polvester
-------------------	------------------

Body Features	Actuator Material	Phosphor
	Actuator Color	Black
	Actuator Travel	2 mm [.079 in]
Contact Features	Contact Base Material	Copper Alloy
	Contact Plating	Gold
Termination Features	Termination Type	PC
Mechanical Attachment	Mounting Angle	Vertical
	Mounting Type	Through Hole
	PCB Mount Retention Type	Guide Posts
	PCB Mount Retention	With
Dimensions	PCB Tail Length	3.51 mm [.136 in]
	Length	24 mm [.9449 in]
	Actuator Length	9.02 mm [.355 in]
	Width	9.35 mm [.3681 in]
Identification Marking	Stamped Marking	With
Industry Standards	UL Flammability Rating	UL 94-HB
Packaging Features	Packaging Method	Tray
Product Compliance	Statement of Compliance PDF VIEW ALL PRODUCT COMPLIANCE	