

PART NUMBER SCHEME :

10159560-X X X X X X X X F

LEAD FREE

X	POWER POSITION
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
A	10

X	FOR RECEPTACLE, SEE DWG. NO. 10159561			
COMBINATION OF MATED HEIGHT	HEADER 1	HEADER 2	HEADER 3	HEADER 4
	HEIGHT: 1.3	HEIGHT: 2.3	HEIGHT: 3.3	HEIGHT: 4.3
RECEPTACLE 1				
HEIGHT: 3.7	5	6	7	8
RECEPTACLE 2				
HEIGHT: 7.7	9	10	11	12
RECEPTACLE 3				
HEIGHT: 11.7	13	14	15	16
RECEPTACLE 4				
HEIGHT: 15.7	17	18	19	20

X	PLATING: CONTACT AREA
1	GOLD 0.05um MIN
2	GOLD OR GXT 0.2um MIN
3	GOLD OR GXT 0.375um MIN
4	GOLD OR GXT 0.75um MIN

X	POLARIZATION PEG/ DATE CODE
L	WITH PEG/ WITHOUT DATE CODE
P	WITH PEG/ WITH DATE CODE
M	WITHOUT PEG/ WITHOUT DATE CODE
N	WITHOUT PEG/ WITH DATE CODE

X	SOLDER TAIL PLATING: POWER PIN
I	GOLD FLASH

X	PACKAGING
R	T&R WITH MYLAR
T	TUBE WITHOUT MYLAR
Q	T&R WITHOUT MYLAR

X	EMPTY PIN OPTIONAL
0	NONE
2	2#
3	3#
4	4#
5	5#
6	6#
7	7#
8	8#
9	9#

X	CUSTOMER OPTIONAL
0	GENERAL
E	E CUSTOMIZED

DATE CODE: XXXXXX  
 DAY (01~32)  
 MONTH (01~12)  
 YEAR (00~99)

- NOTES:
- MATERIAL:
    - HOUSING: THERMOPLASTICNOTES, WHITE.
    - POWER CONTACT: COPPER ALLOY
    - HOLD DOWN: COPPER ALLOY
  - PLATING:
    - UNDER PLATING: 1-3um NI UNDER PLATING;
    - CONTACT AREA: ACCORDING TO PART NUMBER;
    - SOLDER TAIL:
      - POWER CONTACT: ACCORDING TO PART NUMBER;
      - HOLD DOWN: TIN PLATING
  - PRODUCT SPEC GS-12-1675
  - APPLICATION GS-20-0696
  - THIS HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 20 SECONDS IN A IR REFLOW SOLDERING APPLICATION.
  - THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-47-0004.
  - COPLANARITY AREA OF TERMINATION 0.10MM MAX.

spec ref	dr	Li-Qing Lei	2021/03/25	projection	mm	size	A3	scale	1:1
tolerance std	eng	Li-Qing Lei	2021/07/28		← →	ecn no	ELX-N-41469-1	rel level	Released
TOLERANCES UNLESS OTHERWISE SPECIFIED									
surface	linear	0.X	±0.5	Amphenol FCI	HEADER	dwg no	10159560	rev	C
		0.XX	±0.25						
		0.XXX	±0.10						
	angular	0°	±2°	cat. no.	Product - Customer Drw	sheet 1 of 2			

Amphenol FCI

© 2020 Amphenol Corporation

