


GSD



STAMP: KINGS 126-35-9
YRWK (DATE CODE)

GSD

1. FOR USE WITH TIMES AA-5887 CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-440-2.
3. FOR CABLE TRIMMING USE K7J-150 & KTD-138.
4. FOR CRIMPING USE DIE KTH-1077.
5. INTERFACE PER MIL-STD-348, FIG. 313-1.
6. CENTER CONTACT (1-5704-2MA9) SUPPLIED UNASSEMBLED.
7. MARK PACKAGE: KINGS 126-35-9
XX XX (DATE CODE)
8. MATERIALS:
 - INSULATORS: TEFLON, ASTM-D-1457
 - K-GRIP SLEEVE: COM. BRONZE TUBE, ALLOY 220
 - C-RING: PHOS. BRONZE, QQ-B-750
 - GASKET: SIL. RUB., ZZ-R-765
 - OUTER CONTACT }
CENTER CONTACT } BER. COP., ASTM-B-196
 - ALL OTHER METAL PARTS: BRASS, ASTM-B16
9. FINISHES:
 - CENTER CONTACTS: HARD GOLD PLATE PER MIL-G-45204
 - ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT FINISH (TR-5)
10. ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE: 50 OHMS
 - VOLTAGE RATING: 500 VRMS
 - FREQUENCY RANGE: DC TO 11 GHz

MAY 2007 THIS DRAWING BECAME THE PROPERTY OF PROPERTY OF
WINCHESTER ELECTRONICS CORPORATION, WALLINGFORD, CT 06492