



Wire Sizes

Solid min	0.2 mm ²
Solid max	1.5 mm ²
Stranded (flexible) min	0.2 mm ²
Stranded (flexible) max	1.5 mm ²
Stranded with ferrule min	0.2 mm ²
Stranded with ferrule max	1.5 mm ²

Dimensions

Stripped length	5.0 mm
PCB hole diameter	1.3 mm

Materials

Clamp	Brass
Wire guard	Stainless Steel
Screw	Steel

Insulating Material

Material	PA 6.6
Flammability class	UL 94 V-0

Temperatures

Operating temperature (without mech. load)	-40 °C - 105 °C
Store temperature	-40 °C - 105 °C

Wave Soldering Process

Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Spacing 10.0 mm

Colours

GREY, RAL 7016

BLUE, RAL 5015

Colours according to RAL, there may be variations on colour due to production conditions.
 Special colours on request.

Ratings

					
UseGroup	B	C	D		
Rated voltage	300 V	150 V	300 V	1.000 V	
Rated current	15 A	15 A	10 A	17.5 A	
Rated wire size				min	max
- solid	AWG 22-14	AWG 22-14	AWG 22-14	0.5 mm ²	1.5 mm ²
- stranded	AWG 22-14	AWG 22-14	AWG 22-14	0.5 mm ²	1.5 mm ²
Torque	0.40 Nm	0.40 Nm	0.40 Nm	0.40 Nm	
Screw size	M2.6	M2.6	M2.6	M2.6	
Test voltage	1.60 kV	1.30 kV	1.60 kV	3.5 kV	

Order Data (Spacing 10.0 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	15.60	AK500/2DS-10.0-H-GREY	50500020241 G	250
3	25.60	AK500/3DS-10.0-H-GREY	50500030241 G	250
4	35.60	AK500/4DS-10.0-H-GREY	50500040241 G	250
5	45.60	AK500/5DS-10.0-H-GREY	50500050241 E	100
6	55.60	AK500/6DS-10.0-H-GREY	50500060241 E	100
7	65.60	AK500/7DS-10.0-H-GREY	50500070241 D	50
8	75.60	AK500/8DS-10.0-H-GREY	50500080241 D	50
9	85.60	AK500/9DS-10.0-H-GREY	50500090241 D	50
10	95.60	AK500/10DS-10.0-H-GREY	50500100241 D	50
11	105.60	AK500/11DS-10.0-H-GREY	50500110241 D	50
12	115.60	AK500/12DS-10.0-H-GREY	50500120241 D	50



PTR HARTMANN

A Phoenix Mecano Company

Technical Data // **AK500/..DS-10.0-H-GREY**

Spacing 10.0 mm

Technical drawing

