

SRMB4/16

- 32 Connections
- Direct mounting





Phoenix Mecano Brand

Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	4.0 mm ²	Stripped Length	9.0 mm
Clamping Range min	0.2mm ²	Width	6.0 mm
Clamping Range max	4.0 mm ²	Height	23.0 mm
		Length	111.8 mm
		Length Hole Direct Mounting	104.7 mm

Colours

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015

Connection Diagram



Order Data

Article Designation	Article Number	PU
SRMB4/16-BEIGE	41037.2	20
SRMB4/16-BLUE	41037.5	20

Accessoires

Article Designation	Article Number	PU
External Cross-Connector insulated AQI2/6/11	492125.0	50
External Cross-Connector insulated AQI3/6/11	492126.0	50
External Cross-Connector insulated AQI4/6/11	492140.0	10
External Cross-Connector insulated AQI10/6/11	492141.0	10
Quick Labelling PSB6/50	494702.7	500

Ratings

Ratings	UR	CSA	IEC
Rated Voltage	300 V	300 V	400 V
Rated Current	30 A	25 A	32 A
Rated Wire Size	AWG 22-12	AWG 22-12	4.0 mm ²
Rated Impulse Voltage			6 V
Pollution Degree			3