



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to CECC 22 240

Documents

Assembly instruction 88 02

Material and plating

Connector parts

	Material	Plating
Center contact	Brass	AuroDur, gold plated
Outer contact	Beryllium copper	AuroDur, gold plated
Body	Brass	Nickel, 2.5-5 µm
Coupling nut	Brass	Nickel, 2.5-5 µm
Dielectric	PTFE	
Dielectric	LCP	
Crimping ferrule	Copper	Nickel, 2.5-5 µm

Electrical data

Impedance	75 Ω
Frequency	DC to 12 GHz
Return loss	≥ 33 dB, DC to 2 GHz ≥ 23 dB, 2 to 4 GHz ≥ 20 dB, 4 to 8 GHz ≥ 15 dB, 8 to 12 GHz
Insertion loss	≤ 0.1 dB, DC to 8 GHz
Insulation resistance	≥ 10x10 ³ MΩ
Center contact resistance	≤ 4 mΩ
Outer contact resistance	≤ 2 mΩ
Test voltage	1000 V rms
Working voltage	330 V rms
RF-leakage	≥ 90 dB up to 1 GHz (slide-on) ≥ 100 dB up to 1 GHz (screw version)

- Limitations are possible due to the used cable type -

Mechanical data

Mating cycles	≥ 500
Engaging and disengaging force	2.2 N to 12 N (screw-on, slide-on) 18 N to 50 N (quick-lock)
Center contact captivation	≥ 30 N
Coupling mechanism retention force	≥ 300 N (screw version, quick-lock)

Environmental data

Temperature range	-40°C to +85°C	
Climatic class	IEC 60068-2-1 40/85/21 IEC 60068-2-2 IEC 60068-2-3	
Vibration 2002/95/EC (RoHS)	IEC 60068-2-6 compliant	10 Hz to 2000 Hz, 100m/s ²

Tooling

Crimping tool	11W150-000
Crimp insert	11W150-502

Suitable cables

RG 187 A/U, RG 179 B/U

Packing

Standard	1 pce in bag
Weight	7.6 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	30/08/04	A. König	11/07/07	d00	07-0154	S. Huber-Siegl	11/07/07
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de		Page 2 / 2