

S1D13742

S1D13742 VGA LCD Controller

The S1D13742 is a VGA color LCD graphics controller with an embedded 768 KB display buffer. The S1D13742 supports a 8/16-bit Intel 80 CPU architecture while providing high performance bandwidth into display memory allowing for fast screen updates.


Products requiring a rotated display image can take advantage of the SwivelView™ feature which provides hardware rotation of the display memory transparent to the software application. Resolutions supported include 800x480 single buffered and 352x416 double buffered.

The S1D13742 uses a double-buffer architecture to prevent any visual tearing during streaming video screen updates. These features combined with the low cost, low power design of the S1D13742, provide an ideal display solution for a wide variety of applications within embedded markets.

FEATURES

- Embedded 768 KB SRAM display buffer
- Low operating voltage
- 8/16-bit Intel 80 interface (used for display or register data)
- Input data formats:
 - RGB: 8:8:8, 6:6:6, 5:6:5
 - YUV 4:2:2, 4:2:0
- Supports TFT panels
- 18/36-bit RGB interface
- Supports resolutions up to 800x480
- Hardware / software power save mode
- 16/18 bpp color depths
- SwivelView™: 90°, 180°, 270° counter-clockwise hardware rotation of display image
- Double-buffer available to prevent image tearing during streaming input
- Pixel doubling: horizontal and vertical averaging for smooth doubling of a single window
- Pixel halving: no limitation on number of windows
- Internal programmable PLL
- Single MHz clock input: CLKI
- General purpose input/output pins

SYSTEM BLOCK DIAGRAM



DESCRIPTION

Display Buffer

- 768 KB of embedded SRAM

Panel Support

- Supports TFT panels
- 18/36-bit interface
- Supports resolutions up to 800x480

Input Data Formats

- RGB: 8:8:8, 6:6:6, 5:6:5 (8:8:8 will be truncated to 16 or 18 bpp)
- YUV 4:2:2, 4:2:0 (internal YUV to RGB converter stored as 16 or 18 bpp)

Miscellaneous

- Internal programmable PLL
- Single MHz clock input: CLKI
- CLKI available as CLKOUT (separate CLKOUTEN pin associated with output)
- Hardware/software power save mode
- Input pin to enable/disable power save mode
- General purpose input/output pins are available (GPIO[7:0])
- COREVDD 1.5 volts and IOVDD 1.65 ~ 3.6 volts
- QFP20 144-pin package

CPU Interface

- 8/16-bit Intel 80 interface (used for display or register data)
- Chip select used to select device, when inactive, any input data/command is ignored

Display Features

- 16/18 bpp color depths
- All display writes are handled by window apertures/position (for complete or partial display updates). All window coordinates are referenced to top left corner of the displayed image (even in a rotated display, the top-left corner is maintained and no host side translation need take place)
- SwivelView™: 90°, 180°, 270° counter-clockwise hardware rotation of display image. All displayed windows can have independent rotation. No additional programming necessary when enabling these modes.
- Double-buffer available to prevent image tearing during streaming input. Resolutions supported must fit inside 384KB (1/2 of total available display buffer). Typical resolution of 352x416.
- Pixel doubling: horizontal and vertical averaging for smooth doubling of a single window
- Pixel halving: no limitation on number of windows

For more information on the S1D13742 and other Epson Display Controllers, visit the Epson Global website.

https://global.epson.com/products_and_drivers/semicon/products/display_controllers/



For Sales and Technical Support, contact the Epson representative for your region.

https://global.epson.com/products_and_drivers/semicon/information/support.html



NOTICE:

Document code: X63A-C-001-04.2

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You are requested not to use, to resell, to export and/or to otherwise dispose of the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies.

©Seiko Epson Corporation 2005 - 2018. All rights reserved.