



RECOMMENDED
CABLE STRIPPING DIM'S

1. CRIMPED CONTACT PIN
HEX CRIMP SIZE .100"

NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)
 1. BRASS PER QQ-B-626
 2. BRASS PER QQ-B-613
 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 4. GOLD PL. 3 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
 5. TEFLON MIL-P-19468

NO.	DESCRIPTION	MATERIAL	FINISH	QTY	DRAWING NO
13	CONTACT PIN			1	B5201-13-3/26
12	NUT			1	B5201-12-19/111
11	WASHER			1	WS-16/115X05
10	GASKET	SILICONE	RED	1	B5201-10
9	BRAID CLAMP			1	B5201-9-111/91
8	WASHER			1	WS-145/75X05
7	WASHER			1	WS-128/9X08
6	RING	DELTRIN	NATURAL	1	T50000-6-A
5	RETAINER RING			1	B50000-5
4	GASKET	RUBBER	RED	1	GS-105/8X15
3	INSULATOR		NATURAL	1	B5201-3T-50
2	BODY			1	B5201-2
1	SHELL			1	T50000-1-B

DIMENSIONS ARE IN MILLIMETERS
 UNLESS OTHERWISE SPECIFIED
 TOLERANCES
 0.5-6 = ±0.2
 6-30 = ±0.4
 30-120 = ±0.6
 120-315 = ±1
 315-1000 = ±1.6
 1000-2000 = ±2.4

PART NO.	T1141A2-001-NT3G-7A-50
APPROVED	DATE 10-11-01'
CHECKED	DATE 10-11-01'
DRAWN	DATE 10-11-01'
FILE NO	

Amphenol	
TITLE	TNC CLAMP PLUG
DRAWING NO.	KJ-T1141A2-001-NT3G-214U-50
ITEM NO.	