


Euro Series

Twin plug and socket connectors to Euro-Standard 80 A, 150 V Accordance EN1175-1

For electrically-operated industrial trucks
Service voltage: 24, 36, 48, 72, 80 and 96 V can be coded
Housing of high grade plastic

Socket complete with cable clamp



Battery

Length: 75 mm max.
Width: 77 mm max.
Height: 25 mm max.
Weight: 124 g approx.

Cat. No.				
mm ²	With coding pins for wet batteries		With coding pins for dry batteries	
	Without	With	Without	With
Pilot contacts				
16	75306	75307	75328	75332
25	75309	75312	75330	75334
Housing		75425		

A removable handle in black or red can be supplied on request.

Vehicle plug complete without cable clamp




Vehicle

Length: 74mm max.
Width: 77 mm max.
Height: 25 mm max.
Weight: 103 g approx.

Cat. No.				
mm ²	With coding pins for wet batteries		With coding pins for dry batteries	
	Without	With	Without	With
Pilot contacts				
16	75201	75215	75190	75194
25	75202	75217	75192	75196
Housing		75427		

* REMA universal coding

Plug complete with cable clamp



Charger

Length: 74 mm max.
Width: 77 mm max.
Height: 25 mm max.
Weight: 120 g approx.

Cat. No.				
mm ²	With coding pins for wet batteries		With coding pins for dry batteries	
	Without	With	Without	With
Pilot contacts				
16	75198	75209	75206	75208
25	75199	75214	75211	75213
Housing		75427		

Plug complete

Twin plug and socket FT80A, 150V

For electrically-operated industrial trucks
Service voltage: 12, 24, 36, 48, 72, 96 and 80 V can be coded
Shell of high grade plastic

Socket complete with cable clamp



Cat. No.				
mm ²	With coding pins for wet batteries		With coding pins for dry batteries	
	Without	With	Without	With
Pilot contacts				
16	81200-00	81210-00	81205-00	81215-00
25	81201-00	81211-00	81206-00	81216-00
Housing without cable clamp		81230-00		

Handle can be supplied in black or red