



### TYPE YDS-A & YDS-AT

#### HYSPLICE™

FULL TENSION SLEEVE  
FOR ALL ALUMINUM  
COMPRESSED AND  
COMPACT CONDUCTORS.



Full-Tension HYSPLICE™ sleeve made of aluminum tubing with staked-in cable stop. Sizes 1/0 and larger tapered for gradual transition of stress. Installed with HYSPLICE™ tools and dies. Pre-filled with PENETROX® joint compound and capped.

E-56

CATALOG NUMBER	CONDUCTOR	L	DIE INDEX	TOOLS, DIE SET CATALOG NO., & CRIMPS PER END							
				MD6	Y35, Y750	Y45	Y46	Y48B	Y60BHU		
YDS6WA	6 Sol.	3	161	W161	2	U161	1*	†	‡	—	—
YDS4WA	4 Sol.	2-5/8	162	W162	4	U162	1*	†	‡	—	—
YDS2WA	2 Sol.	3-7/8	163	W163	6	U163	2*	†	‡	—	—
YDS6CA	6 (7)	3	161	W161	2	U161	1*	†	‡	—	—
YDS4CA	4 (7)	2-5/8	162	W162	4	U162	1*	†	‡	—	—
YDS2CA	2 (7)	3-7/8	163	W163	6	U163	2*	†	‡	—	—
YDS25AT	1/0 (7)	7-1/4	BG, or 243	BG, or W243	12 6	BG, or U243	3 3	†	‡	—	—
YDS26AT	2/0 (7)	9-1/4	245	W245	8	U245	4	†	‡	—	—
YDS27AT	3/0 (7, 19)	7-1/4	247	W247	8	U247	4	†	‡	C247	2 L247 2
YDS28AT	4/0 (7, 19)	10-1/2	249	W249	12	U249	6	†	‡	C249	3 L249 3
YDS29AT	250 (19)	7-1/2	616	—	—	U616	6	†	‡	—	—
YDS291AT	266.8 (7,19)	8-5/8	251	—	—	U251	7	†	‡	C251	4 L251 4
YDS301AT	336.4 (19,37)	9-7/8	321	—	—	U321	8	†	‡	C321	4 L321 4
YDS31AT	350 (19)	11	490	—	—	U490	9	†	‡	C490	5 L490 5
YDS311AT	397.5 (19)	12-1/4	468	—	—	U468	10	†	‡	—	—
YDS331AT	477 (19)	12-3/4	317	—	—	U317	9	†	‡	C317	3 L317 3
YDS351AT	556.5 (19, 37)		261	—	—	U261	9	†	‡	C261	3 L261 3
YDS361AT	636 (37)	13-1/2	469	—	—	—	—	S469 12	P469 12	C469	4 L469 4
YDS391AT	795 (37, 800 (61))	13-5/8	342	—	—	—	—	S342 12	P342 12	C342	4 L342 4
YDS431AT	954 (37, 61)	17-5/8	352	—	—	—	—	S352 15	P352 15	C352	5 L352 5
YDS451AT	1272 (61)	18-1/2	422	—	—	—	—	—	—	—	L422 6

\* Multiple crimp die set; makes more than one crimp per tool compression. Figure indicates number of compressions.

† U Die with adapter PT-6515.

‡ U Die with adapter PUADP-1.