


PTCR Motor Start Pellets



Vishay Cera-Mite offers a complete line of PTCR motor start pellets designed for OEM pressure contact mounting. Compressor and refrigerator manufacturers, as well as selected HVAC aftermarket distributors have chosen to design and build their own proprietary motor start devices. Such cost effective units allow for unique mounting styles, special terminal arrangements, and combination devices including start capacitors or overload protectors.

FOR USE IN :



Motor Start Relays



Combination Assemblies

APPLICATION DATA

- Complete range of size/resistance combinations for 120 and 240 volt compressor motors
- Rugged silver electrodes well suited for long life pressure contact mounting
- Withstand voltage is 2 times Voltage Max. rating
- Application engineering assistance provided for custom pellet designs

PTCR MOTOR START PELLETS					
RESISTANCE		VOLTAGE MAX. (V _{RMS})	CURRENT MAX. (A _{RMS})	DIAMETER (D) x THICKNESS (T) (mm)	PART NUMBER
R ₂₅ (Ω)	R _{DYN} (Ω)				
5	4	200	10	16 x 2.5	307C1674*
5.5	4.2	180	12	16 x 2.5	307C1670
6.8	5	200	10	16 x 2.5	307C1700*
8	5.8	150	10	16 x 2.5	307C1280
10	7.2	200	10	16 x 2.5	307C1711*
10	7.2	200	10	16 x 2.5	307C1713
20	13.5	250	7.5	16 x 2.5	307C1490
47	30	300	6.5	16 x 2.5	307C1136
68	42	300	5.5	16 x 2.5	307C1043
4	3.2	180	15	17.5 x 2.5	307C1614
5	4	180	12	17.5 x 2.5	307C1668
6.8	5	200	10	17.5 x 2.5	307C1644
10	7.2	200	10	17.5 x 2.5	307C1651
15	10.5	265	6	17.5 x 2.5	307C1190
20	13	320	8	17.5 x 2.5	307C1720
25	17	300	7.5	17.5 x 2.5	307C1066
33	22	300	6.5	17.5 x 2.5	307C1040
47	30	350	4	17.5 x 2.5	307C1284
68	42	400	4	17.5 x 2.5	307C1283
3.3	2.6	160	12	20 x 2.5	307C1411
4.7	3.5	180	12	20 x 2.5	307C1484
5.6	4.1	180	12	20 x 2.5	307C1544
6.8	5	200	10	20 x 2.5	307C1399
10	7.2	230	9	20 x 2.5	307C1489
12	8.5	250	8.5	20 x 2.5	307C1476
15	10.5	300	8	20 x 2.5	307C1530
22	15	400	8	20 x 2.5	307C1531
33	22	355	6	20 x 2.5	307C1282
47	30	400	5	20 x 2.5	307C1533
68	42	430	4	20 x 2.5	307C1292
3.9	3 (at 50 V)	175	16	20 x 3.2	307C1487
12	10.3 (at 100 V)	350	8	20 x 3.2	307C1529
14	12 (at 100 V)	350	8	20 x 3.2	307C1545
30	15.9 (at 240 V)	380	12	20 x 3.2	307C1640
25	18 (at 240 V)	400	9	20 x 5.0	307C1518
38	25 (at 240 V)	400	9	20 x 5.0	307C1024
50	35 (at 240 V)	400	7.5	20 x 5.0	307C1409
75	50 (at 240 V)	400	5.5	20 x 5.0	307C1410

R₂₅ = zero power resistance ± 30 % at 25 °C; other tolerances available

R_{DYN} = nominal dynamic (effective) resistance, 120 V applied unless otherwise noted

* High performance ceramic formulation, lower transition temperature provides reduced power consumption for energy conscious applications

Notes

- All motor start pellets receive 100 % resistance and 100 % voltage pulse burn-in simulating actual motor start-up
- Selected pellets carry UL recognition per File E107611
- Usage requires packaging materials appropriate for maximum pellet surface temperature of 180 °C
- All 307C Motor Start Pellets are RoHS compliant e4



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.