

## RGE600K Product Details



**RGE600K**

TE Internal Number: 322631-000

**Obsolete**

[Contact Product Information Center](#)

### PolySwitch Resettable Devices

[Always ELV Compliant](#) ([Find RoHS Compliant Alternates/Statement of Compliance](#))

**Product Highlights:**

- Radial Application
- Family Name = RGE
- Radial Construction, Through Hole Construction
- IH (Room Temperature) = 6 Amps.
- IT (Room Temperature) = 10.20 Amps.

[View all Features](#)

### Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

### Documentation & Additional Information

**Product Drawings:**

- [RGE600K](#) (PDF, English)

**Catalog Pages/Data Sheets:**

- None Available

**Product Specifications:**

- None Available

**Application Specifications:**

- None Available

**Instruction Sheets:**

- None Available

**CAD Files:**

- None Available

**Additional Information:**

- [Product Line Information](#)

**Related Products:**

- [Tooling](#)

[List all Documents](#)

### Product Features (Please use the Product Drawing for all design activity)

**Product Type Features:**

- UL Recognized = File No. E74889
- CSA File No. = 78165C

**Electrical Characteristics:**

- [IH \(Room Temperature\) \(Amps.\)](#) = 6
- [IT \(Room Temperature\) \(Amps.\)](#) = 10.20
- [Vmax Operating \(V\)](#) = 16
- [Rmin \(?\)](#) = 0.01
- [Rmax \(?\)](#) = 0.0185
- [R1 Max \[Post Trip\] \(?\)](#) = 0.028
- Power Dissipation (Typical) (W) = 2.80

**Termination Related Features:**

- Construction = Radial, Through Hole

**Body Related Features:**

- Lead Type = Standard Kinked Lead

**Contact Related Features:**

- [Family Name](#) = RGE

**Configuration Related Features:**

- Coating = Coated

**Industry Standards:**

- [RoHS/ELV Compliance](#) = ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Always was ELV compliant
- TUV Certificate No. = R72041433

**Conditions for Usage:**

- [Operating Temperature \(Max.\) \(°C\)](#) = 85

**Operation/Application:**

- Application = Radial

**Packaging Related Features:**

- Packaging Method = Bulk

**Other:**

- Brand = Raychem