

# In-Line Optical Attenuators, Flat Wavelength, LC APC

LC APC, 1 dB

CORNING

Corning offers in-Line, flat wavelength optical attenuators that are easily inserted between the connector and adapter in an “in-line” configuration and are compatible with SC, ST<sup>®</sup> compatible, FC, MU, LC and angled SC and FC connectors. A fundamental element of these Corning attenuators is the zirconia ferrule containing a specially selected attenuating fiber. This special fiber minimizes the effect of modal interference and gives the component a flat spectral response. It is extremely stable over the wavelength range of 1260 to 1360 nm and 1430 to 1580 nm. These in-line, flat wavelength attenuators are available in ultra PC ( $\leq$  -55 dB) and angled PC ( $\leq$  -65 dB) finish to meet the most demanding network reflectance requirements.

## Features and Benefits

**Fully compatible with LC fiber optic connectors**  
No intermateability concerns

**Numerical identification mark on housing**  
Easy indication of attenuation levels

**Attenuator incorporated inside standard LC adapter housings**  
Compatible with standard distribution panels

## Standards

**Design and Test Criteria** Telcordia GR-910 issue 2 performance requirements



Part Number: ATN-A12-01



Part Number: ATN-A12-01

# In-Line Optical Attenuators, Flat Wavelength, LC APC

LC APC, 1 dB

CORNING

## Specifications

General Specifications	
Attenuator Type	In-Line
Compatibility	LC
Packaging	Single Pack
Product Type	Attenuators

Temperature Range	
Operation	-25 °C to 70 °C (-13 °F to 158 °F)

Design - Connector	
Ferrule Material	Zirconia
Housing Material	Composite
Housing Color	Metal

Optical Specifications - Connector	
Attenuation	1 dB
Attenuation Tolerance	± 0.5 dB
Insertion Loss	0.05 dB

Chemical Characteristics	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

## Ordering Information

Part Number	ATN-A12-01
Product Description	LC APC In-Line Optical Attenuator, Flat Wavelength
EAN Code	4056418195308

# In-Line Optical Attenuators, Flat Wavelength, LC APC

LC APC, 1 dB



## Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, LC APC



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • [www.corning.com/opcomm](http://www.corning.com/opcomm)

A complete listing of the trademarks of Corning Optical Communications is available at [www.corning.com/opcomm/trademarks](http://www.corning.com/opcomm/trademarks).

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.