



NOTES:

- FOR USE WITH RG-8, 8A, 11, 11A & 213/U CABLE.
- FOR CABLING INSTRUCTIONS SEE 3-7-2.
- FOR CABLE TRIMMING USE KTJ-124 & KTD-179.
- FOR CRIMPING USE DIE KTH-1078.
- MATERIALS:
INSULATOR: HIGH DENSITY POLYETHYLENE, MIL-P-22748
GASKETS: SIL. RUB., ZZ-R-765
K-GRIP SLEEVE: COM. BRONZE TUBE, ALLOY 220
CONTACT: BER. COP., ASTM-B-196
SPRING: STAINLESS STEEL, TYPE 302
ALL OTHER PARTS: BRASS, ASTM-B16
- FINISHES:
CENTER CONTACT: HARD GOLD PLATE PER MIL-G-45204
SPRING: PASSIVATE PER QQ-P-35
ALL OTHER METAL PARTS: KINGS TARNISH RESISTANT FINISH (TR-5)
- ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: NON-CONSTANT
VOLTAGE RATING: 20 KVDC
INSULATION RESISTANCE: 10^6 MEGOHMS
CURRENT CARRYING CAPACITY: 25 AMPS @ 30°C TEMP RISE

SD1765-1

REVISIONS	
ISSUE	CHANGES
4	CN 34190 C REDRAWN JCA 10/30/92
5	CN 37941 E HVN 11/24/99
6	CN 39710 C DRK 11/22/06
H	REVISED PER ER ER20507 GGR 12/03/2009

CUSTOMER SALES DRAWING

SCALE 2:1	
APPROX SURFACE AREA	
USED ON	
REF:	
PLUG, 20 KV	
DRAWN JCA	DATE 10/30/92
DESIGN LI	DATE 11/02/92
APPR.	DATE
KINGS by WINCHESTER	Winchester Electronics 82 Barnes Industrial Road North Wallingford, CT 06492

SD1765-1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Winchester Interconnect:](#)

[1765-1](#)