

KCMA-18-250-5A-1VA-0.5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image, Similar to illustration

The cable-type current transformer is primarily used in retrofitting to avoid splitting the primary conductors.

- Thanks to its dimensions and ease of handling, the cable-type current transformer is particularly suitable for use in places that are difficult to access or in case of limited space
- In combination with the securing clamps, the "click" system even enables "one-handed" installation.

General ordering data

Version	Primary current: 250 A, Secondary current max.: 5 A, Load: 1 VA, Tolerance class: 0,5, detachable current transformer
Order No.	2753050000
Type	KCMA-18-250-5A-1VA-0.5
GTIN (EAN)	4050118896299
Qty.	1 pc(s).

Creation date July 21, 2021 7:51:52 AM CEST

Catalogue status 16.07.2021 / We reserve the right to make technical changes.

KCMA-18-250-5A-1VA-0.5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	59 mm	Depth (inches)	2.323 inch
Height	80.1 mm	Height (inches)	3.154 inch
Width	49 mm	Width (inches)	1.929 inch
Net weight	316 g		

Temperatures

Operating temperature	-5 °C...50 °C
-----------------------	---------------

Dimensions of live conductors

Installation location	Indoor use	Round conductor	18.5 mm
Type of conductor	Insulated conductor only		

Technical data

Protection degree	IP20
-------------------	------

Insulation coordination

Tolerance class	0,5
-----------------	-----

Classifications

ETIM 6.0	EC002048	ETIM 7.0	EC002048
ETIM 8.0	EC002048	ECLASS 9.0	27-21-09-02
ECLASS 9.1	27-21-09-02	ECLASS 10.0	27-21-09-02
ECLASS 11.0	27-21-09-02		

Approvals

ROHS	Conform
------	---------

Downloads

User Documentation	Instruction sheet German
Catalogues	Catalogues in PDF-format

Data sheet

KCMA-18-250-5A-1VA-0.5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

