




**.380 Flanged Spade  
.031 Electro-Tinned Copper  
16-14 AWG (Blue)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
6	X			B	✓	✓	4000	50439	
		X		B	✓	✓	3000	50439-8	
			X	B	✓	*	3000	50439-8A	
	X			W	✓	✓	4000	50440	
		X		W	✓	✓	3000	50440-8	
			X	W	✓	*	3000	50440-8A	
8	X			B	✓	✓	4000	50451	
		X		B	✓	✓	3000	50451-8	
			X	B	✓	*	3000	50451-8A	
	X			W	✓	✓	4000	50452	
		X		W	✓	✓	3000	50452-8	
			X	W	✓	*	3000	50452-8A	
10	X			B	✓	✓	4000	50463	
		X		B	✓	✓	3000	50463-8	
			X	B	✓	*	3000	50463-8A	
	X			W	✓	✓	4000	50464	
		X		W	✓	✓	3000	50464-8	
			X	W	✓	*	3000	50464-8A	

**.500 Flanged Spade  
.031 Electro-Tinned Copper  
16-14 AWG (Blue)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
10	X			B	✓	✓	4000	50652	
		X		B	✓	✓	3000	50652-8	
			X	B	✓	*	3000	50652-8A	
	X			W	✓	✓	4000	50653	
		X		W	✓	✓	3000	50653-8	
			X	W	✓	*	3000	50653-8A	
1/4	X			B	✓	✓	4000	50664	
		X		B	✓	✓	3000	50664-8	
			X	B	✓	*	3000	50664-8A	
	X			W	✓	✓	4000	50665	
		X		W	✓	✓	3000	50665-8	
			X	W	✓	*	3000	50665-8A	

Recommended Strip Length  $\frac{9}{32} \pm \frac{1}{32}$   
\* Contact Factory for Latest Agency Approvals.

G  
N  
R  
&  
E  
D  
A  
P  
S