



**Description**  
**BNC 50 Ohm Cable Jack -**  
**Single Hole Mount Straight Cut Straight**

**Ordering Data**  
**BNC 50 Ohm Cable Jack - Single Hole Mount Straight Cut Straight**

Part Number	Cable RG-/U	Dimension						Finish	Mtg. Hole	Assembly Instructions	Note
		A		B		C					
		mm	in.	mm	in.	mm	in.				
28JS104-1	58	36.51	1.438	19.05	0.750	15.88	0.625	Silver	D4	AI-12	1
28JS104-2	59, 62	36.51	1.438	19.05	0.750	15.88	0.625	Silver	D4	AI-12	2
28JS104-3	174, 187, 188	36.51	1.438	19.05	0.750	15.88	0.625	Silver	D4	AI-12	3
28JS120-1	58	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-12	
28JS120-2	59	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-12	
28JS120-3	174, 188	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-12	
28JS120-4	223	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-12	
28JS120-9	302	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-12	
28JS120-12	178, 196	28.58	1.125	20.64	0.813	17.46	0.688	Nickel	D4	AI-12	
28JS129-4	180, 195	37.31	1.469	19.05	0.750	15.88	0.625	Silver	D4	AI-14	
28JS138-1	179	37.31	1.469	11.91	0.469	15.88	0.625	Silver	D4	AI-330	
28JS154-1	0.141 OD SR	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-14	4
28JS154-2	0.085 OD SR	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-14	4
28JS179-1	0.141 SR	28.58	1.125	17.07	0.672	4.37	0.172	Silver	D4	AI-331	5
28JS185-4	122	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-119	
28JS185-5	303	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-119	
28JS185-6	302	28.58	1.125	20.64	0.813	17.46	0.688	Silver	D4	AI-119	

Note 1 - Isolated Ground. Also available in clamp cable termination as 28JS129-1 or M39012 type as 28JS185-2.  
 Note 2 - Isolated Ground. Also available in clamp cable termination as 28JS129-2 or M39012 type as 28JS185-3.  
 Note 3 - Isolated Ground. Also available in clamp cable termination as 28JS129-3.  
 Note 4 - Cable termination is plug-in/clamp.  
 Note 5 - Cable termination is solder on bushing/clamp.