


Rev. F

**OM-X8GXXXXX-X Series
HF/UHF OCXO Low Power**


Description: The OM-X8GXXXXX Series of Oven Controlled Crystal Oscillators (OCXO) provides High and Ultra High Frequency with SC-cut stability performance, extremely low phase noise and power consumption, with either CMOS or Sine-wave output in a standard 1.4x1” package – “Europack”.

Features

- Very Low Power Consumption
- Very Low Phase Noise
- Excellent SC-cut Frequency Stability
- Ultra High Frequency – up to 1 GHz
- CMOS, Sine-Wave outputs available
- Stratum3E available



Creating a Part Number



OM-X8GXXXXX-X Series HF/UHF OCXO Low Power

Rev. F

Specifications

| Parameter | Symb | Condition | Min | Typ | Max | Unit | Note |
|-----------|------|-----------|-----|-----|-----|------|------|
|-----------|------|-----------|-----|-----|-----|------|------|

Absolute Maximum Ratings

| | | | | | | | |
|--------------------------|-----|--|------|--|-----|----|--|
| Input Break Down Voltage | Vcc | | -0.5 | | 5.5 | V | |
| Storage temp. | Ts | | -40 | | 85 | °C | |
| Contr. Voltage | Vc | | 1 | | 9 | V | |

Electrical

| | | | | | | | | |
|----------------------|-------|---|---|--------------------------------------|---------------|---------------------------------|---|--|
| Frequency Range | F | CMOS Sine-wave | 30 30 | | 200 1,000 | MHz | | |
| Input Voltage | Vcc | | 3.135 4.75 | 3.30 5.0 | 3.465 5.25 | V | A 0 | |
| Input Current | Icc | | | | 90 160 | mA | @ 100 MHz, 3.3V @ 622 MHz, 3.3V | |
| Frequency Stability | ΔF/F | vs. Temperature vs. Vcc aging | | ±50 ±2 ±0.1 ±0.5 | | ppb ppb/V ppm/year ppm | See chart First Year 15 years | |
| Calibration | ΔF/F | As shipped, 25°C | | ±0.1 | | ppm | | |
| Load | | CMOS Sine | 15pF/10KOhm Internally AC-coupled 50 Ohm | | | | | |
| Duty cycle | | @50% | 45 | 50 | 55 | % | CMOS | |
| Rise/Fall time | Tr/Tf | 20 to 80 % | | 3 | | ns | CMOS | |
| Logic "1" level | Voh | CMOS | 0.9Vcc | | | V | | |
| Logic "0" level | Vol | CMOS | | | 0.1Vcc | V | | |
| Output power | P | Sinewave Into 50 Ohm | 0 4 | 3 7 | | dBm | 3.3V 5.0V | |
| Start up time | Ts | | | 2 | 10 | ms | | |
| Phase jitter | | 1σ | | 0.4 0.2 | 1 0.4 | ps | 100 Hz to 20 MHz 12 KHz to 20 MHz | |
| Subharmonics | | Sine CMOS, Sine | | -45 | -40 none | dBc | F>250MHz F< 250 MHz | |
| Spurious | | | | | -60 | dBc | | |
| Harmonics | | Sine-wave | | -30 | -25 | dBc | | |
| SSB Phase Noise | | @ 10 Hz @ 100 Hz @ 1 KHz @ 10 KHz @ 100 KHz | | -100 -120 -140 -160 -165 | | dBc/Hz | @ 100 MHz | |
| SSB Phase Noise | | @ 10 Hz @ 100 Hz @ 1 KHz @ 10 KHz @ 100 KHz | | -80 -90 -120 -145 -150 | | dBc/Hz | @622 MHz; Sine | |
| Input Impedance | | | > 10KOhm | | | | | |
| Control voltage | Vc | | 0 | | 4.0 | V | Vcc code "0" | |
| | | | 0 | | 2.8 | V | Vcc code "A" | |
| Modulation bandwidth | MB | | | 2Hz | | | Contact Factory for wider MB | |
| Deviation | | 0V to Vc max | ±0.5 | ±1.0 | | ppm | | |



FREQUENCY
CONTROLS, INC.

357 Beloit Street, P.O. Box 457, Burlington, WI 53105-0457 U.S.A. Phone 262/763-3591 FAX 262/763-2881

Email: nelsales@nelfc.com www.nelfc.com

Rev. F

OM-X8GXXXXX-X Series HF/UHF OCXO Low Power

Environmental and Mechanical

| | |
|------------------------------|---|
| Operating temp. range | 0°C to 70°C , -40°C to 85°C, see chart, page 1 |
| Mechanical Shock | Per MIL-STD-202, Method 213, Cond. E |
| Thermal Shock | Per MIL-STD-883, Method 1011, Cond. A |
| Vibration | Per MIL-STD-883, Method 2007, Cond. A |
| Soldering Conditions | 260°C for 10 s leads only |
| Hermetic Seal | Leak rate less than 5×10^{-8} atm.cc/s of helium |

Electrical Connections

| | |
|----------------|---|
| Pin Out | Pin #1- Voltage Control ; Pin #2 – Vref ; Pin #3 – Vcc; Pin#4 – Output, CMOS or Sine; Pin#5 - GND |
|----------------|---|



**FREQUENCY
CONTROLS, INC.**

357 Beloit Street, P.O. Box 457, Burlington, WI 53105-0457 U.S.A. Phone 262/763-3591 FAX 262/763-2881

Email: nelsales@nelfc.com www.nelfc.com