

Part Number : <u>457503112</u> Product Description : Mini-Fit Plus Crimp Terminal, 16 AWG, Bag, Copper (Cu) Alloy, Tin (Sn) Series Number : 45750 Status : Active Product Category : Crimp Terminals Packaging Alternative : 0457503111 (Reel)



Documents & Resources

Drawings

Drawing 457503112_sd.pdf Packaging Design Drawing PK-5556-003-001.pdf

Specifications

Product Specification PS-45750-001-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|---|
| China RoHS | ® |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2023)3788-DC (14 Jun 2023) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Crimp Terminals |
| Series | 45750 |
| Description | Mini-Fit Plus Crimp Terminal, 16 AWG, Bag, Copper (Cu) Alloy, Tin (Sn) |
| Application | Power, Wire-to-Board, Wire-to-Wire |
| Comments | Current = 13A max. per circuit when header is mated to a receptacle loaded with 45750 series terminals crimped to 16 AWG wire. See Molex product specification PS-45750-001 for additional current de-rating information. Series 45750 is Hot- Swappable |
| Product Family | Mini-Fit Family Power Connectors |
| Product Name | Mini-Fit Plus |
| UPC | 822350286046 |

Electrical

| Current - Maximum per Contact | 13.0A |
|-------------------------------|-------|
| Voltage - Maximum | 600V |

Physical

| Durability (mating cycles max) | 100 |
|--------------------------------|--------------|
| Gender | Female |
| Material - Metal | Copper Alloy |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Net Weight | 0.150/g |

| Packaging Type | Bag |
|-----------------------------|----------------------|
| Plating min - Mating | 2.540µm |
| Plating min - Termination | 2.540µm |
| Termination Interface Style | Crimp or Compression |
| Wire Insulation Diameter | 3.50mm |
| Wire Size (AWG) | 16 |
| Wire Size mm ² | N/A |

Solder Process Data

| | Lead-Free Process Capability | N/A |
|--|------------------------------|-----|
|--|------------------------------|-----|

Use with Part(s)

| Description | Part Number |
|--|--------------|
| Mini-Fit TPA Dual Row Receptacle Housings | <u>30067</u> |
| Mini-Fit BMI Dual Row Receptacle Housings | 42474 |
| Mini-Fit BMI Dual Row Receptacle Housings | 43760 |
| Mini-Fit BMI Dual Row Receptacle Housings | 44516 |
| Mini-Fit Jr. Receptacle Housings | 5557 |

Application Tooling

Global

| Description | Part Number |
|--|-------------|
| Extraction Tool for Mini-Fit Jr. Terminals | 0011030044 |
| Hand Crimp Tool for Mini-Fit Jr. Male and Female Crimp Terminals, 16 AWG | 2002182200 |

This document was generated on Oct 02, 2023