




Glass Passivated Single-Phase Bridge Rectifier



Case Style KBPM

FEATURES

- UL Recognition file number E54214
- Ideal for printed circuit board
- High surge current capability
- High case dielectric strength
- Solder Dip 260 °C, 40 seconds
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



TYPICAL APPLICATIONS

General purpose use in ac-to-dc bridge full wave rectification for Switching Power Supply, Home Appliances, Office Equipment, and Telecommunication applications.

MECHANICAL DATA

Case: KBPM

Epoxy meets UL 94V-0 flammability rating

Terminals: Silver plated (E4 Suffix) leads, solderable per J-STD-002B and JESD22-B102D

Polarity: As marked on body

| MAJOR RATINGS AND CHARACTERISTICS | |
|-----------------------------------|----------------|
| $I_{F(AV)}$ | 1.5 A |
| V_{RRM} | 50 V to 1000 V |
| I_{FSM} | 50 A |
| I_R | 5 μ A |
| V_F | 1.0 V |
| T_j max. | 150 °C |

| MAXIMUM RATINGS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | | | | | | |
|---|----------------|---------------|---------|---------|---------|---------|---------|---------|------------------|
| PARAMETER | SYMBOL | KBP 005M | KBP 01M | KBP 02M | KBP 04M | KBP 06M | KBP 08M | KBP 10M | UNIT |
| | | 3N246 | 3N247 | 3N248 | 3N249 | 3N250 | 3N251 | 3N252 | |
| * Maximum repetitive peak reverse voltage | V_{RRM} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| * Maximum RMS voltage | V_{RMS} | 35 | 70 | 140 | 280 | 420 | 560 | 700 | V |
| * Maximum DC blocking voltage | V_{DC} | 50 | 100 | 200 | 400 | 600 | 800 | 1000 | V |
| Max. average forward output rectified current at $T_A = 40\text{ }^\circ\text{C}$ | $I_{F(AV)}$ | 1.5 | | | | | | | A |
| * Peak forward surge current single half sine-wave $T_A = 25\text{ }^\circ\text{C}$ $T_j = 150\text{ }^\circ\text{C}$ | I_{FSM} | 50 30 | | | | | | | A |
| Rating for fusing ($t < 8.3\text{ ms}$) | I^2t | 10 | | | | | | | $A^2\text{sec}$ |
| * Operating junction and storage temperature range | T_j, T_{STG} | - 55 to + 150 | | | | | | | $^\circ\text{C}$ |

* JEDEC registered values

| ELECTRICAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted) | | | | | | | | | | | |
|--|---|----------------|----------|---------|---------|---------|------------|---------|---------|------|----|
| PARAMETER | TEST CONDITIONS | SYMBOL | KBP 005M | KBP 01M | KBP 02M | KBP 04M | KBP 06M | KBP 08M | KBP 10M | UNIT | |
| | | | 3N246 | 3N247 | 3N248 | 3N249 | 3N250 | 3N251 | 3N252 | | |
| * Maximum instantaneous forward voltage drop per leg | at 1.0 A at 1.57 A | V _F | | | | | 1.0 1.3 | | | | V |
| * Maximum DC reverse current at rated DC blocking voltage per leg | T _A = 25 °C T _A = 125 °C | I _R | | | | | 5.0 500 | | | | μA |
| Typical junction capacitance per leg | at 4.0 V, 1 MHz | C _J | | | | | 15 | | | | pF |

* JEDEC registered values

| THERMAL CHARACTERISTICS (T _A = 25 °C unless otherwise noted) | | | | | | | | | | |
|---|--------------------------------------|----------|---------|---------|---------|----------|---------|---------|------|------|
| PARAMETER | SYMBOL | KBP 005M | KBP 01M | KBP 02M | KBP 04M | KBP 06M | KBP 08M | KBP 10M | UNIT | |
| | | 3N246 | 3N247 | 3N248 | 3N249 | 3N250 | 3N251 | 3N252 | | |
| Typical thermal resistance per leg ⁽¹⁾ | R _{θJA} R _{θJL} | | | | | 40 13 | | | | °C/W |

Note:

(1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with, 0.47 x 0.47" (12 x 12 mm) copper pads

| ORDERING INFORMATION | | | | |
|----------------------|-----------------|------------------------|---------------|----------------------|
| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| KBP06M-E4/45 | 1.895 | 45 | 30 | Tube |
| KBP06M-E4/51 | 1.895 | 51 | 600 | Anti-static PVC Tray |
| 3N250-E4/45 | 1.895 | 45 | 30 | Tube |
| 3N250-E4/51 | 1.895 | 51 | 600 | Anti-static PVC Tray |

RATINGS AND CHARACTERISTICS CURVES

(T_A = 25 °C unless otherwise noted)




Figure 1. Derating Curve Output Rectified Current




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 3. Typical Forward Characteristics Per Leg




Figure 5. Typical Junction Capacitance Per Leg





Figure 4. Typical Reverse Leakage Characteristics Per Leg

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.