



GRT1-OD4G-1

SmartSlice 4 x digital outputs 0.5 A, 24 VDC, PNP, with overcurrent and short-circuit protection

Specifications

I/O system	GRT1 I/O Bus
Type of module	Digital I/O
I/O connection type	Push-in
Connection method	2-wire, 3-wire
Number of digital inputs	0
Digital input type	None
Number of digital outputs	4
Digital output type	PNP
Permitted voltage at output	20.4-26.4 V
Output current	0.5 A
Short-circuit protected outputs	✓
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Degree of protection (IP)	IP20
Height	84 mm
Width	15 mm
Depth	74.4 mm
Product Weight (unpacked)	86 g

Accessories



GRT1-PD2

SmartSlice I/O power feed module, 24 VDC input



EtherCAT Junction Slave Brochure

EN PDF 1.04 MB



GRT1 series (Precautions For UL CSA Standards) Instruction Sheet

EN PDF 46.5 KB



GRT1 series (Safety Precautions) Instruction Sheet

EN PDF 522 KB



GRT1- SmartSlice Remote I/O Datasheet

EN PDF 446 KB



SmartSlice Brochure

EN PDF 2.03 MB



Sysmac Catalogue

EN PDF 43.5 MB