



300 Ring
20-14 AWG

Spade and Ring Series Uninsulated

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
4	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-4	
						Pre Tinned Brass	3G2-4	
					.032	Brass	3G3-4	
						Pre Tinned Brass	3G4-4	
6	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-6	
						Pre Tinned Brass	3G2-6	
					.032	Brass	3G3-6	
						Pre Tinned Brass	3G4-6	
8	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-8	
						Brass	3G1-8-2*	
					.032	Pre Tinned Brass	3G2-8	
						Pre Tinned Brass	3G2-8-2*	
					.032	Brass	3G3-8	
						Pre Tinned Brass	3G4-8	
10	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-10	
						Pre Tinned Brass	3G2-10	
					.032	Nickel Plated Brass	3G1-10-5†	
						Brass	3G3-10	
					.032	Pre Tinned Brass	3G4-10	
						* Diagonal Wire Grip		
4	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-3	
						Pre Tinned Brass	3G2-3	
					.032	Brass	3G3-3	
						Pre Tinned Brass	3G4-3	
6	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-5	
						Pre Tinned Brass	3G2-5	
					.032	Brass	3G3-5	
						Pre Tinned Brass	3G4-5	
.154	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-5A	
8	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-7	
						Pre Tinned Brass	3G2-7	
					.032	Brass	3G3-7	
						Pre Tinned Brass	3G4-7	
10	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-9	
						Pre Tinned Brass	3G2-9	
					.032	Brass	3G3-9	
						Pre Tinned Brass	3G4-9	
12	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$.020	Brass	3G1-15	
						Pre Tinned Brass	3G2-15	

† Not UL or CSA recognized.