

Plasma Panel Display Modules

DC Character Module with Drive Electronics
TTL Level Data Interface and Integrated DC Converter



The APD-016A070 DC Plasma display offers viewing qualities designers seek such as high contrast, viewing angle of 150° minimum, and long distance readability. It is bright (50 foot lamberts minimum) characters are presented in a pleasing neon orange color against a black background. Plasma is much more readable and eye-pleasing than liquid crystal or vacuum fluorescent displays and is filterable to red, amber or neutral density.

These plasma display panels are driven by refreshing all 14 segments, the decimal point and the comma much like a CRT display. Each character segments are serially entered from segment A thru R (no I, L, O or Q segments) plus the decimal point and comma. Then a latch pulse advances the character, latches the data and turns on the outputs. The designer need only supply TTL level signals for SEGMENT DATA, SEGMENT CLOCK, CHARACTER LATCH and ANODE DATA. The SEGMENT DATA is entered, with the SEGMENT CLOCK up to frequencies as high as 8MHz. After all 14 segments, 1 period and 1 comma have been entered, the CHARACTER LATCH signal is toggled and the SEGMENT DATA is latched. At the time the data is latched, the display is briefly disabled and the character is advanced by the CHARACTER LATCH signal. Once each frame the ANODE DATA must be asserted to synchronize the character location with the SEGMENT DATA. The recommended scanning frequency is approximately 70Hz, but may be as high as 200Hz.

FEATURES

- TTL level interface.
- + 5 VDC only option available.
- High brightness and contrast.
- Large characters.
- On board DC converter.

ELECTRICAL SPECIFICATIONS

Voltage Required: Vdd: + 8 VDC to + 24 VDC.

Power Required: Typical = 4 watts. Maximum = 9 watts.

OPTICAL SPECIFICATIONS

Viewing Area: 10.70" [271.78mm] W x 0.70" [17.78mm] H.

Character Array: 1 x 16.

Character Size: 0.70" [17.78mm] W x 0.44" [11.18mm] H.


Luminance: 50 foot lamberts minimum.


STANDARD ELECTRICAL SPECIFICATIONS*

DESCRIPTION	SYMBOL	MIN.	TYP.	MAX.	UNITS
Display supply	Vdd	+ 8	+ 18 ± 5%	+ 25	VDC
Logic 1 Input	Vih	2.0	—	—	VDC
Logic 0 Input	Vil	—	—	0.8	VDC

*Recommended operating voltages. All maximums are absolute maximum.

DIMENSIONS in inches [millimeters]





PIN DESCRIPTION

P3, POWER CONNECTOR
 AMP #640445-5 or equivalent.
 (Mates with AMP 640428-5, MOLEX 09-50-3051 or equivalent.)

PIN	SIGNAL	DESCRIPTION
1	GND	Logic and Power
2	—	—
3	Vdd	Display Supply
4	KEY	Used to key connector
5	GND	Logic and Power

P2, DATA CONNECTOR
 AMP #103309-2 or equivalent.
 (Mates with AMP 746195-2, MOLEX 39-27-1146 or equivalent.)

PIN	DESCRIPTION	PIN	DESCRIPTION
1	—	2	GROUND
3	ANODE DATA	4	GROUND
5	—	6	GROUND
7	CHARACTER LATCH	8	GROUND
9	SEGMENT CLOCK	10	GROUND
11	SEGMENT DATA	12	GROUND
13	No connect	14	GROUND

ORDERING INFORMATION

DESCRIPTION	PART NUMBER
Display Module with Drivers and TTL Interface	APD-016A070
Data Connector Kit	280105-05
Power Connector Kit	280108-13



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.