



.380 Spade
.031 Electro-Tinned Copper
22-18 AWG (Red)

Spade and Ring Series
Pre-Insulated

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.117	.147	.180						
6	X			B	✓	✓	5000	50387	
		X		B	✓	✓	4000	50387-8	
			X	B	✓	*	4000	50387-8A	
	X			W	✓	✓	5000	50388	
		X		W	✓	✓	4000	50388-8	
			X	W	✓	*	4000	50388-8A	
8	X			B	✓	✓	5000	50399	
		X		B	✓	✓	4000	50399-8	
			X	B	✓	*	4000	50399-8A	
	X			W	✓	✓	5000	50400	
		X		W	✓	✓	4000	50400-8	
			X	W	✓	*	4000	50400-8A	
10	X			B	✓	✓	5000	50411	
		X		B	✓	✓	4000	50411-8	
			X	B	✓	*	4000	50411-8A	
	X			W	✓	✓	5000	50412	
		X		W	✓	✓	4000	50412-8	
			X	W	✓	*	4000	50412-8A	

.500 Spade
.031 Electro-Tinned Copper
22-18 AWG (Red)

Spade and Ring Series
Pre-Insulated

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.117	.147	.180						
10	X			B	✓	✓	5000	50609	
		X		B	✓	✓	4000	50609-8	
			X	B	✓	*	4000	50609-8A	
	X			W	✓	✓	5000	50610	
		X		W	✓	✓	4000	50610-8	
			X	W	✓	*	4000	50610-8A	
1/4	X			B	✓	✓	5000	50621	
		X		B	✓	✓	4000	50621-8	
			X	B	✓	*	4000	50621-8A	
	X			W	✓	✓	5000	50622	
		X		W	✓	✓	4000	50622-8	
			X	W	✓	*	4000	50622-8A	

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
 * Contact Factory for Latest Agency Approvals.

S P A D E & R I N G