


MDC-J01H-0250FF



RealFlex® 3 Fiber Optic Drop Cable, SC/APC to stub, RBR Riser, Ivory, 250 ft

Product Classification

Regional Availability	Latin America North America
Product Type	Fiber drop cable assembly
Product Brand	RealFlex®
Product Series	MDC

General Specifications

Color, boot A	Green
Color, connector A	Green
Connector A, quantity	1
Interface, Connector A	SC/APC
Jacket Color	Ivory
Total Fibers, quantity	1
Transmission Standards	TIA/EIA-568-B.3

Dimensions

Cord Length	76.2 m 250 ft
Diameter Over Jacket	3 mm 0.118 in

Mechanical Specifications

Minimum Bend Radius, loaded	7.62 mm 0.3 in
Minimum Bend Radius, unloaded	29.97 mm 1.18 in

Optical Specifications

Fiber Mode	Singlemode
Fiber Type	G.657.A2/B2

MDC-J01H-0250FF

Environmental Specifications

Operating Temperature	-20 °C to +70 °C (-4 °F to +158 °F)
Storage Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Environmental Space	Riser
Jacket UV Resistance	UV stabilized
Qualification Standards	Telcordia GR-449-CORE

Packaging and Weights

Packaging quantity	1
---------------------------	---

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted

