



Part #, Drawing, Series

Search

PRODUCTS

MARKETS

SEARCH TOOLS

ABOUT US

BLOG

CONTACT US


SLIDE

HOME > PRODUCTS > SWITCHES > SLIDE > PRODUCT DETAILS

SK-22D01-MG 5 NS

SK SERIES

MINIATURE SLIDE SWITCH



Those designing innovative applications in the consumer electronics, computer peripherals and telecommunications industry turn to C&K's SK series miniature slide switches when they need a long-lasting, high-performing switch solution. The SK series come in shorting or non-shorting options and can be custom designed by C&K's expert teams.

FEATURES AND BENEFITS

- Broad range of products
- Compact miniature slide switch
- Shorting or non-shorting
- Custom design available

TYPICAL APPLICATIONS

- Consumer electronics
- Computer peripherals
- Telecommunication

SPECIFICATIONS

Contact Rating:	0.3A @ 4 VDC
Electrical Life:	10,000 cycles with load
Contact Resistance:	70 milliohms max.
Insulation Resistance:	100 megohms min.
Dielectric Strength:	500 V AC (50-60 Hz) between open terminals and between the frame and terminal
Operating Temperature:	-20°C to 70°C

SK-22D01-MG 5 NS

Most Common:	Yes
Current Rating:	0.3A
Circuit:	DPDT
Mounting Type:	Thru-hole, Right Angle
Sealing:	Unsealed
Illumination:	None
Switch Function:	On-On
Electrical Life Cycles:	10,000
Contact Timing:	Non-Shorting (BBM)
Voltage Rating - AC:	
Voltage Rating - DC:	30V
Actuator Type:	Standard
Actuator Length:	5.00mm
Contact Material:	Copper
Contact Finish:	Silver clad
Termination Style:	Thru-hole

Image shown represents the product series and may not indicate the actual part number



TOOLBOX

[Product Selection Guide](#)
[Sales Locator](#)



DOWNLOADS

[Datasheet](#)
[Complete Product Line](#)

CONTACT TECH SUPPORT

SEARCH DISTRIBUTOR STOCK

REQUEST SAMPLE

3D MODEL

Additional Features:

Packaging:

Bulk



[Sitemap](#)

[Terms & Conditions](#)

[Legal](#)

[Privacy](#)

[Careers](#)

[Contact Us](#)

