

$\phi 30 \mu\text{m}$  InGaAs AVALANCHE PHOTO DIODE  
14-PIN DIP MODULE WITH TEC


DESCRIPTION

The NR8360JP-BC is an InGaAs avalanche photodiode module with single mode fiber. A thermoelectric cooler is integrated enabling the temperature control of the APD chip. It is designed for long-reach optical communications and optical test instruments, especially OTDR.

FEATURES

- High quantum efficiency  $\eta = 85\% @ \lambda = 1310 \text{ nm}$   
 $\eta = 80\% @ \lambda = 1550 \text{ nm}$
- Small dark current  $I_D = 2 \text{ nA}$
- High-speed response  $f_c = 1.2 \text{ GHz} @ M = 20$
- Internal thermoelectric cooler
- Hermetically sealed 14-pin Dual In-line Package


<R> PACKAGE DIMENSIONS (UNIT: mm)



The information in this document is subject to change without notice. Before using this document, please confirm that this is the latest version.  
Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.

**OPTICAL FIBER CHARACTERISTICS**

Parameter	Specification	Unit
Mode Field Diameter	9.5±1	μm
Cladding Diameter	125±2	μm
Maximum Cladding Noncircularity	2	%
Maximum Core/Cladding Concentricity	1.6	%
Outer Diameter	0.9±0.1	mm
Cut-off Wavelength	1 100 to 1 270	nm
Minimum Fiber Bending Radius	30	mm
Fiber Length	1 000 MIN.	mm
Flammability	UL1581 VW-1	



**ORDERING INFORMATION**

Part Number	Available Connector
NR8360JP-BC	With FC-UPC Connector

**ABSOLUTE MAXIMUM RATINGS**

Parameter	Symbol	Ratings	Unit
Forward Current	I <sub>F</sub>	10	mA
Reverse Current	I <sub>R</sub>	500	μA
Operating Case Temperature	T <sub>C</sub>	-20 to +55	°C
Storage Temperature	T <sub>stg</sub>	-40 to +85	°C
Lead Soldering Temperature	T <sub>slid</sub>	260 (10 sec.)	°C
Cooler Current	I <sub>C</sub>	1.0	A
Cooler Voltage	V <sub>C</sub>	2.0	V

**ELECTRO-OPTICAL CHARACTERISTICS (T<sub>APD</sub> = 25°C, T<sub>C</sub> = -20 to +55°C, unless otherwise specified)**

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Reverse Breakdown Voltage	V <sub>BR</sub>	I <sub>D</sub> = 100 μA	50	70	100	V
Temperature Coefficient of Reverse Breakdown Voltage	δ <sup>1</sup>			0.2		%/°C
Dark Current	I <sub>D</sub>	V <sub>R</sub> = V <sub>BR</sub> × 0.9		5	10	nA
		V <sub>R</sub> = V <sub>BR</sub> × 0.9, T <sub>C</sub> = 55°C, I <sub>C</sub> = 0.8 A		2	5	
Multiplied Dark Current	I <sub>DM</sub>	M = 2 to 10		0.2	2.0	nA
Terminal Capacitance	C <sub>t</sub>	V <sub>R</sub> = V <sub>BR</sub> × 0.9, f = 1 MHz		1.0	1.7	pF
Cut-off Frequency	f <sub>c</sub>	M = 10	1.0			GHz
		M = 20		1.2		
Quantum Efficiency	η	λ = 1 310 nm	70	85		%
		λ = 1 550 nm	65	80		
Sensitivity	S	λ = 1 310 nm	0.73	0.89		A/W
		λ = 1 550 nm		1.00		
Multiplication Factor	M	λ = 1 310 nm, I <sub>op</sub> = 1.0 μA, V <sub>R</sub> = V (@ I <sub>D</sub> = 1 μA)	20	40		
Excess Noise Factor <sup>2</sup>	x	λ = 1 310 nm, 1 550 nm, I <sub>op</sub> = 1.0 μA,		0.7		
	F	M = 10, f = 35 MHz, B = 1 MHz		5		

\*1  $\delta = \frac{V_{BR}(25^{\circ}\text{C} + \Delta T^{\circ}\text{C}) - V_{BR}(25^{\circ}\text{C})}{\Delta T^{\circ}\text{C} \cdot V_{BR}(25^{\circ}\text{C})}$

\*2  $F = M^x$

**ELECTRO-OPTICAL CHARACTERISTICS (T<sub>APD</sub> = 25°C, T<sub>C</sub> = -20 to +55°C, unless otherwise specified)**

Parameter	Symbol	Conditions	MIN.	TYP.	MAX.	Unit
Thermistor Resistance	R		9.5	10.0	10.5	kΩ
B Constant	B		3 350	3 450	3 550	K
Cooler Current	I <sub>c</sub>	ΔT = 45°C		0.6	0.8	A
Cooler Voltage	V <sub>c</sub>	I <sub>c</sub> = 0.8 A		1.1	1.5	V
Cooling Capacity	ΔT <sup>-1</sup>	I <sub>c</sub> = 0.8 A	45			°C

\*1  $\Delta T = |T_C - T_{APD}|$

**<R> REFERENCE**

Document Name	Document No.
Opto-Electronics Devices Pamphlet	PX10160E

• **The information in this document is current as of August, 2008. The information is subject to change without notice. For actual design-in, refer to the latest publications of NEC Electronics data sheets or data books, etc., for the most up-to-date specifications of NEC Electronics products. Not all products and/or types are available in every country. Please check with an NEC Electronics sales representative for availability and additional information.**

- No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Electronics. NEC Electronics assumes no responsibility for any errors that may appear in this document.
- NEC Electronics does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from the use of NEC Electronics products listed in this document or any other liability arising from the use of such products. No license, express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Electronics or others.
- Descriptions of circuits, software and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software and information in the design of a customer's equipment shall be done under the full responsibility of the customer. NEC Electronics assumes no responsibility for any losses incurred by customers or third parties arising from the use of these circuits, software and information.
- While NEC Electronics endeavors to enhance the quality, reliability and safety of NEC Electronics products, customers agree and acknowledge that the possibility of defects thereof cannot be eliminated entirely. To minimize risks of damage to property or injury (including death) to persons arising from defects in NEC Electronics products, customers must incorporate sufficient safety measures in their design, such as redundancy, fire-containment and anti-failure features.
- NEC Electronics products are classified into the following three quality grades: "Standard", "Special" and "Specific".

The "Specific" quality grade applies only to NEC Electronics products developed based on a customer-designated "quality assurance program" for a specific application. The recommended applications of an NEC Electronics product depend on its quality grade, as indicated below. Customers must check the quality grade of each NEC Electronics product before using it in a particular application.

"Standard": Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots.

"Special": Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support).

"Specific": Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems and medical equipment for life support, etc.

The quality grade of NEC Electronics products is "Standard" unless otherwise expressly specified in NEC Electronics data sheets or data books, etc. If customers wish to use NEC Electronics products in applications not intended by NEC Electronics, they must contact an NEC Electronics sales representative in advance to determine NEC Electronics' willingness to support a given application.

(Note)

- (1) "NEC Electronics" as used in this statement means NEC Electronics Corporation and also includes its majority-owned subsidiaries.
- (2) "NEC Electronics products" means any product developed or manufactured by or for NEC Electronics (as defined above).

**SAFETY INFORMATION ON THIS PRODUCT**

<p><b>Caution</b> GaAs Products</p>	<p>This product uses gallium arsenide (GaAs). GaAs vapor and powder are hazardous to human health if inhaled or ingested, so please observe the following points.</p> <ul style="list-style-type: none"> <li>• Follow related laws and ordinances when disposing of the product. If there are no applicable laws and/or ordinances, dispose of the product as recommended below.               <ol style="list-style-type: none"> <li>1. Commission a disposal company able to (with a license to) collect, transport and dispose of materials that contain arsenic and other such industrial waste materials.</li> <li>2. Exclude the product from general industrial waste and household garbage, and ensure that the product is controlled (as industrial waste subject to special control) up until final disposal.</li> </ol> </li> <li>• Do not burn, destroy, cut, crush, or chemically dissolve the product.</li> <li>• Do not lick the product or in any way allow it to enter the mouth.</li> </ul>
<p><b>Caution</b> Optical Fiber</p>	<p>A glass-fiber is attached on the product. Handle with care.</p> <ul style="list-style-type: none"> <li>• When the fiber is broken or damaged, handle carefully to avoid injury from the damaged part or fragments.</li> </ul>