



**.300 Hook
.020 Pre Tinned Brass
16-14 AWG (Blue)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
4	X			B	✓	✓	4000	50804-200	
		X		B	✓	✓	3000	50804-200-8	
				X	B	✓	*	3000	
6	X			B	✓	✓	4000	50812-200	
		X		B	✓	✓	3000	50812-200-8	
			X	B	✓	*	3000	50812-200-8A	
8	X			B	✓	✓	4000	50820-200	
		X		B	✓	✓	3000	50820-200-8	
			X	B	✓	*	3000	50820-200-8A	

**.300 Hook
.031 Electro-Tinned Copper
16-14 AWG (Blue)**

**Spade and Ring Series
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.147	.200	.250						
4	X			B	✓	✓	4000	50804-300	
		X		B	✓	✓	3000	50804-300-8	
				X	B	✓	*	3000	
4	X			W	✓	✓	4000	50805-300	
		X		W	✓	✓	3000	50805-300-8	
			X	W	✓	*	3000	50805-300-8A	
6	X			B	✓	✓	4000	50812-300	
		X		B	✓	✓	3000	50812-300-8	
			X	B	✓	*	3000	50812-300-8A	
6	X			W	✓	✓	4000	50813-300	
		X		W	✓	✓	3000	50813-300-8	
			X	W	✓	*	3000	50813-300-8A	
8	X			B	✓	✓	4000	50820-300	
		X		B	✓	✓	3000	50820-300-8	
			X	B	✓	*	3000	50820-300-8A	
8	X			W	✓	✓	4000	50821-300	
		X		W	✓	✓	3000	50821-300-8	
			X	W	✓	*	3000	50821-300-8A	

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.

**G
I
N
I
R
&
E
A
D
E
S
P
A
D
E
&
S**