

In-Line Optical Attenuators, Flat Wavelength, ST[®] Compatible UPC

ST[®] Compatible UPC, 20 dB

CORNING

Corning offers in-Line, flat wavelength optical attenuators that are easily inserted between the connector and adapter in an “in-line” configuration and are compatible with SC, ST[®] compatible, FC, MU, LC and angled SC and FC connectors. A fundamental element of these Corning attenuators is the zirconia ferrule containing a specially selected attenuating fiber. This special fiber minimizes the effect of modal interference and gives the component a flat spectral response. It is extremely stable over the wavelength range of 1260 to 1360 nm and 1430 to 1580 nm. These in-line, flat wavelength attenuators are available in ultra PC (\leq -55 dB) and angled PC (\leq -65 dB) finish to meet the most demanding network reflectance requirements.

Features and Benefits

Fully compatible with ST[®] Compatible fiber optic connectors

No intermateability concerns

Numerical identification mark on housing

Easy indication of attenuation levels

Attenuator incorporated inside standard ST[®] Compatible adapter housings

Compatible with standard distribution panels

Standards

Design and Test Criteria Telcordia GR-910 issue 2 performance requirements



Part Number: ATN-61-20



Part Number: ATN-61-20

In-Line Optical Attenuators, Flat Wavelength, ST[®] Compatible UPC

ST[®] Compatible UPC, 20 dB

CORNING

Specifications

General Specifications

Attenuator Type	In-Line
Compatibility	ST [®] Compatible
Packaging	Single Pack
Product Type	Attenuators

Temperature Range

Operation	-25 °C to 70 °C (-13 °F to 158 °F)
-----------	------------------------------------

Design - Connector

Ferrule Material	Zirconia
Housing Material	Metal
Housing Color	Metal

Optical Specifications - Connector

Attenuation	20 dB
Attenuation Tolerance	± 2 dB
Insertion Loss	2 dB

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---

Ordering Information

Part Number	ATN-61-20
Product Description	ST [®] Compatible UPC In-Line Optical Attenuator, Flat Wavelength
EAN Code	4056418195391

In-Line Optical Attenuators, Flat Wavelength, ST[®] Compatible UPC

ST[®] Compatible UPC, 20 dB



Shipping Information

Units per Delivery	1/1
Package Contents	Attenuator, ST [®] Compatible



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks.

All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.