

			<table><tr><th colspan="4">REVISIONS</th></tr><tr><th>REV</th><th>DESCRIPTION</th><th>DATE</th><th>APPROVED</th></tr><tr><td>01₀</td><td>RELEASED</td><td>7/12/96</td><td></td></tr></table>				REVISIONS				REV	DESCRIPTION	DATE	APPROVED	01 ₀	RELEASED	7/12/96																																																																																																																									
			REVISIONS																																																																																																																																							
REV	DESCRIPTION	DATE	APPROVED																																																																																																																																							
01 ₀	RELEASED	7/12/96																																																																																																																																								
<table><tr><th>ELECTRICAL</th><th>MECHANICAL</th><th>ENVIRONMENTAL</th><th colspan="4">DESIGN CONTROL REQUIRED</th></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions</td><td>Temperature Rating</td><td>HOUSING</td><td>STAINLESS STEEL PER</td><td>PASSIVATE PER</td><td></td></tr><tr><td>Frequency Range (GHz) DC to 26.5</td><td>MIL-STD-348A, Fig. 319.2</td><td>-65°C To +125°C</td><td>DIELECTRIC</td><td>ASTM-A484 AND ASTM-</td><td>QQ-P-35</td><td></td></tr><tr><td>Voltage Rating (VRMS MIN)</td><td>Mating Characteristics:</td><td>Vibration MIL-STD-202,</td><td></td><td>TFE FLUOROCARBON</td><td>N/A</td><td></td></tr><tr><td>250 @ Sea Level</td><td>Insertion (MAX Lbs) 3.0</td><td>Method 204, Cond. D</td><td>CENTER CONTACT</td><td>PER ASTM-D-1457</td><td></td><td></td></tr><tr><td>VSWR 1.06 +.008 f(GHz)</td><td>Withdrawal (MIN Oz) 2.0</td><td>Shock MIL-STD-202,</td><td>GASKET</td><td>BERYLLIUM COPPER PER</td><td>GOLD PLATE PER</td><td></td></tr><tr><td>Insertion Loss(dB MAX) .035√ f(GHz)</td><td>Force to Engage and</td><td>Method 213, Cond. I</td><td></td><td>ASTM-B-196 OR ASTM-B-197,</td><td>MIL-G-45204</td><td></td></tr><tr><td>RF Leakage (dB MIN)</td><td>Disengage (In/Lbs MAX) 2.0</td><td>Thermal shock MIL-STD-202</td><td></td><td>ALLOY C17300, CONDITION H</td><td></td><td></td></tr><tr><td>(-100 f(GHz))</td><td>Center Contact Captivation:</td><td>Method 107, Cond. B, except</td><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td><td></td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 190</td><td>Axial (Lbs) 4.5</td><td>High Temp shall be 115°C</td><td>UNLESS OTHERWISE SPECIFIED</td><td>DRAWN BY </td><td>DATE 7/10/96</td><td rowspan="2">AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td>Dielectric Withstanding Voltage</td><td>Radial (In/Oz) 2.5</td><td>Moisture Resistance</td><td>DIMENSIONS ARE IN INCHES</td><td>CHECKED BY </td><td>DATE 7/12/96</td></tr><tr><td>(VRMS MIN) @ Sea Level 750</td><td></td><td>MIL-STD-202, Method 106,</td><td>TOLERANCE ON</td><td>APPROD BY </td><td></td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td></td><td>except step 7b (vibration)</td><td>FRAC. DEC. ANGLES</td><td></td><td></td><td></td></tr><tr><td>Center Contact 6.0</td><td></td><td>shall be omitted</td><td>+ 1/64 +.005 + °</td><td></td><td></td><td></td></tr><tr><td>Outer Contact 2.0</td><td></td><td>Corrosion MIL-STD-202,</td><td>These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td><td>USE ASS'Y PROCEDURE</td><td>TITLE 'OSSM' FLANGE MOUNT JACK RECEPTACLE</td><td></td></tr><tr><td>RF High Potential @ Sea Level</td><td>.XXX = in</td><td>Method 101, Cond. B,</td><td></td><td>NO. AP. N/A</td><td>SIZE B</td><td>CODE IDENT NO. 26805</td></tr><tr><td>(VRMS MIN @ 5 MHz) 500</td><td>XX.X = mm (REF)</td><td>5% salt spray</td><td></td><td></td><td>SCALE 4:1</td><td>1052-5108-02</td></tr><tr><td>I.R. (Megohms Min) 10,000</td><td></td><td></td><td></td><td></td><td></td><td>REV 01₀</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td>SHEET 1 OF 1</td></tr></table>							ELECTRICAL	MECHANICAL	ENVIRONMENTAL	DESIGN CONTROL REQUIRED				Nominal Impedance (Ohms) 50	Interface Dimensions	Temperature Rating	HOUSING	STAINLESS STEEL PER	PASSIVATE PER		Frequency Range (GHz) DC to 26.5	MIL-STD-348A, Fig. 319.2	-65°C To +125°C	DIELECTRIC	ASTM-A484 AND ASTM-	QQ-P-35		Voltage Rating (VRMS MIN)	Mating Characteristics:	Vibration MIL-STD-202,		TFE FLUOROCARBON	N/A		250 @ Sea Level	Insertion (MAX Lbs) 3.0	Method 204, Cond. D	CENTER CONTACT	PER ASTM-D-1457			VSWR 1.06 +.008 f(GHz)	Withdrawal (MIN Oz) 2.0	Shock MIL-STD-202,	GASKET	BERYLLIUM COPPER PER	GOLD PLATE PER		Insertion Loss(dB MAX) .035√ f(GHz)	Force to Engage and	Method 213, Cond. I		ASTM-B-196 OR ASTM-B-197,	MIL-G-45204		RF Leakage (dB MIN)	Disengage (In/Lbs MAX) 2.0	Thermal shock MIL-STD-202		ALLOY C17300, CONDITION H			(-100 f(GHz))	Center Contact Captivation:	Method 107, Cond. B, except	COMPONENT	MATERIAL	FINISH		Corona, 70,000 Ft (VRMS MIN) 190	Axial (Lbs) 4.5	High Temp shall be 115°C	UNLESS OTHERWISE SPECIFIED	DRAWN BY	DATE 7/10/96	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599	Dielectric Withstanding Voltage	Radial (In/Oz) 2.5	Moisture Resistance	DIMENSIONS ARE IN INCHES	CHECKED BY	DATE 7/12/96	(VRMS MIN) @ Sea Level 750		MIL-STD-202, Method 106,	TOLERANCE ON	APPROD BY			Contact Resistance (Milliohms MAX)		except step 7b (vibration)	FRAC. DEC. ANGLES				Center Contact 6.0		shall be omitted	+ 1/64 +.005 + °				Outer Contact 2.0		Corrosion MIL-STD-202,	These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE 'OSSM' FLANGE MOUNT JACK RECEPTACLE		RF High Potential @ Sea Level	.XXX = in	Method 101, Cond. B,		NO. AP. N/A	SIZE B	CODE IDENT NO. 26805	(VRMS MIN @ 5 MHz) 500	XX.X = mm (REF)	5% salt spray			SCALE 4:1	1052-5108-02	I.R. (Megohms Min) 10,000						REV 01 ₀							SHEET 1 OF 1
ELECTRICAL	MECHANICAL	ENVIRONMENTAL	DESIGN CONTROL REQUIRED																																																																																																																																							
Nominal Impedance (Ohms) 50	Interface Dimensions	Temperature Rating	HOUSING	STAINLESS STEEL PER	PASSIVATE PER																																																																																																																																					
Frequency Range (GHz) DC to 26.5	MIL-STD-348A, Fig. 319.2	-65°C To +125°C	DIELECTRIC	ASTM-A484 AND ASTM-	QQ-P-35																																																																																																																																					
Voltage Rating (VRMS MIN)	Mating Characteristics:	Vibration MIL-STD-202,		TFE FLUOROCARBON	N/A																																																																																																																																					
250 @ Sea Level	Insertion (MAX Lbs) 3.0	Method 204, Cond. D	CENTER CONTACT	PER ASTM-D-1457																																																																																																																																						
VSWR 1.06 +.008 f(GHz)	Withdrawal (MIN Oz) 2.0	Shock MIL-STD-202,	GASKET	BERYLLIUM COPPER PER	GOLD PLATE PER																																																																																																																																					
Insertion Loss(dB MAX) .035√ f(GHz)	Force to Engage and	Method 213, Cond. I		ASTM-B-196 OR ASTM-B-197,	MIL-G-45204																																																																																																																																					
RF Leakage (dB MIN)	Disengage (In/Lbs MAX) 2.0	Thermal shock MIL-STD-202		ALLOY C17300, CONDITION H																																																																																																																																						
(-100 f(GHz))	Center Contact Captivation:	Method 107, Cond. B, except	COMPONENT	MATERIAL	FINISH																																																																																																																																					
Corona, 70,000 Ft (VRMS MIN) 190	Axial (Lbs) 4.5	High Temp shall be 115°C	UNLESS OTHERWISE SPECIFIED	DRAWN BY	DATE 7/10/96	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																																																																																				
Dielectric Withstanding Voltage	Radial (In/Oz) 2.5	Moisture Resistance	DIMENSIONS ARE IN INCHES	CHECKED BY	DATE 7/12/96																																																																																																																																					
(VRMS MIN) @ Sea Level 750		MIL-STD-202, Method 106,	TOLERANCE ON	APPROD BY																																																																																																																																						
Contact Resistance (Milliohms MAX)		except step 7b (vibration)	FRAC. DEC. ANGLES																																																																																																																																							
Center Contact 6.0		shall be omitted	+ 1/64 +.005 + °																																																																																																																																							
Outer Contact 2.0		Corrosion MIL-STD-202,	These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASS'Y PROCEDURE	TITLE 'OSSM' FLANGE MOUNT JACK RECEPTACLE																																																																																																																																					
RF High Potential @ Sea Level	.XXX = in	Method 101, Cond. B,		NO. AP. N/A	SIZE B	CODE IDENT NO. 26805																																																																																																																																				
(VRMS MIN @ 5 MHz) 500	XX.X = mm (REF)	5% salt spray			SCALE 4:1	1052-5108-02																																																																																																																																				
I.R. (Megohms Min) 10,000						REV 01 ₀																																																																																																																																				
						SHEET 1 OF 1																																																																																																																																				