





Spade and Ring Series Uninsulated

**.240 Spade
22-16 AWG**

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	0	.075-.125	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	2A1-00 2A2-00
	2	.075-.125	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre-Tinned Brass	2A1-2 2A2-2
	4	.075-.125	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre-Tinned Brass	2A1-4 2A2-4
	6	.075-.125	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	2A1-6 2A2-6
	0	None	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	2A1-0 2A2-0
	2	None	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	2A1-1 2A2-1
	4	None	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	2A1-3 2A2-3
	6	None	✓ ✓	6000	$\frac{1}{8} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	2A1-5 2A2-5

Spade and Ring Series Uninsulated

**.300 Spade
24-18 AWG**

STYLE AND DIMENSIONS	STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER
	4	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-4-3 3A2-4-3
	6	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-6-3 3A2-6-3
	8	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-8-3 3A2-8-3
	10	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-10-3 3A2-10-3
	4	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-3-3 3A2-3-3
	6	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-5-3 3A2-5-3
	8	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-7-3 3A2-7-3
	10	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass Pre Tinned Brass	3A1-9-3 3A2-9-3

NOTE: UL & CSA do not recognize 24 AWG terminations.