



**.240 Square Spade
.031 Electro-Tinned Copper
22-18 AWG (Red)**

**Spade and Ring Series
Pre-Insulated**

| STUD | MAX. INSULATION DIAMETER | | | SEAM | UL | CSA | QUANTITY PER REEL | PART NUMBER | STYLE AND DIMENSIONS |
|------|--------------------------|------|------|------|----|-----|-------------------|-------------|---|
| | .117 | .147 | .180 | | | | | | |
| 0 | X | | | B | ✓ | ✓ | 5000 | 50079 |  |
| | | X | | B | ✓ | ✓ | 4000 | 50079-8 | |
| | | | X | B | ✓ | * | 4000 | 50079-8A | |
| | X | | | W | ✓ | ✓ | 5000 | 50080 | |
| | | X | | W | ✓ | ✓ | 4000 | 50080-8 | |
| | | | X | W | ✓ | * | 4000 | 50080-8A | |
| 2 | X | | | B | ✓ | ✓ | 5000 | 50087 | |
| | | X | | B | ✓ | ✓ | 4000 | 50087-8 | |
| | | | X | B | ✓ | * | 4000 | 50087-8A | |
| | X | | | W | ✓ | ✓ | 5000 | 50088 | |
| | | X | | W | ✓ | ✓ | 4000 | 50088-8 | |
| | | | X | W | ✓ | * | 4000 | 50088-8A | |
| 4 | X | | | B | ✓ | ✓ | 5000 | 50095 | |
| | | X | | B | ✓ | ✓ | 4000 | 50095-8 | |
| | | | X | B | ✓ | * | 4000 | 50095-8A | |
| | X | | | W | ✓ | ✓ | 5000 | 50096 | |
| | | X | | W | ✓ | ✓ | 4000 | 50096-8 | |
| | | | X | W | ✓ | * | 4000 | 50096-8A | |
| 6 | X | | | B | ✓ | ✓ | 5000 | 50103 | |
| | | X | | B | ✓ | ✓ | 4000 | 50103-8 | |
| | | | X | B | ✓ | * | 4000 | 50103-8A | |
| | X | | | W | ✓ | ✓ | 5000 | 50104 | |
| | | X | | W | ✓ | ✓ | 4000 | 50104-8 | |
| | | | X | W | ✓ | * | 4000 | 50104-8A | |

**.300 Square Spade
.020 Pre-Tinned Brass
22-18 AWG (Red)**

**Spade and Ring Series
Pre-Insulated**

| STUD | MAX. INSULATION DIAMETER | | | SEAM | UL | CSA | QUANTITY PER REEL | PART NUMBER | STYLE AND DIMENSIONS |
|------|--------------------------|------|------|------|----|-----|-------------------|--------------|---|
| | .117 | .147 | .180 | | | | | | |
| 4 | X | | | B | ✓ | ✓ | 5000 | 50261-200 |  |
| | | X | | B | ✓ | ✓ | 4000 | 50261-200-8 | |
| | | | X | B | ✓ | * | 4000 | 50261-200-8A | |
| 6 | X | | | B | ✓ | ✓ | 5000 | 50273-200 | |
| | | X | | B | ✓ | ✓ | 4000 | 50273-200-8 | |
| | | | X | B | ✓ | * | 4000 | 50273-200-8A | |
| 8 | X | | | B | ✓ | ✓ | 5000 | 50285-200 | |
| | | X | | B | ✓ | ✓ | 4000 | 50285-200-8 | |
| | | | X | B | ✓ | * | 4000 | 50285-200-8A | |
| 10 | X | | | B | ✓ | ✓ | 5000 | 50297-200 | |
| | | X | | B | ✓ | ✓ | 4000 | 50297-200-8 | |
| | | | X | B | ✓ | * | 4000 | 50297-200-8A | |

Recommended Strip Length $\frac{9}{32} \pm \frac{1}{32}$
* Contact Factory for Latest Agency Approvals.

**G
N
I
R
&
E
D
A
D
S
P
A
R
T**